






Order number: 215-MDW-1-SP-KSGI106-390

Manufacturer: Briefkasten Manufaktur Lippe

ab **€4,521.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users
with VAT ID and Non-EU countries)



Design pass-through letterbox GOETHE MDW - RAL at choice - GIRA System 106 - VIDEO Complete kit

The modern wall pass-through letterbox GOETHE with seamlessly integrated Gira System 106 in flush design is ideal for the sophisticated entrance area. The straight-lined design makes this letterbox look particularly elegant. Due to the variable shaft length between 300mm to 390mm or 390mm to 560mm, this letterbox can be used in pretty much all brickwork. 3 GIRA system modules are included, so the letterbox can be used directly. The matching GIRA home station and the control unit to complete this letterbox are included. The modules can be subsequently replaced as desired due to the simple retaining system.

The dimensions of the individual boxes allow a capacity of approx. 24-44 liters, the large insertion guarantees no crumpled mail even with DIN C4 envelopes and magazines or after several days of absence. Due to the water drainage edge, the mail inside is optimally protected from the weather. The insertion flap is equipped with high-quality axle dampers, so quiet closing is guaranteed and there is no annoying rattling due to weather influences.

The letterboxes of the GOETHE collection are characterized by the consistent use of stainless steel. The result is a very high durability and sustainability. The design has been developed by our own engineers with a view to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are directly available in our store.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5

- High-quality pass-through mailbox completely made of stainless steel.
- Shaft made of stainless steel 1.4016 (non-rusting magnetic stainless steel), bright.
- Body made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice.
- Quality manufacturing - Made in Germany by Briefkasten Manufaktur Lippe.
- The mailbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 landscape, here fit even large letters without bending.
- Letter slot & removal door made of stainless steel V2A 1.4301, powder coated in RAL of your choice.
- Letter insertion and removal are from the front. Insertion flap with high-quality axle dampers for very quiet insertion of the mail.
- Removal door can be opened from top to bottom. This prevents the mail from falling towards you.
- Function box (BH 400x200mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice.
- Nameplate made of stainless steel, powder coated in RAL color. Your name and/or a bell are optionally lasered on the nameplate.
- Optionally with house number, lasered (a name inscription can also be deposited here).
- Incl. GIRA home station & control unit enclosed, System 106 door station module, info module & camera module installed.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, powder coated in RAL color.
- Variable shaft length 300-390mm or 390-560mm. Outer dimensions letter chute W 380 mm x H 180mm.
- External dimensions front W 450mm x H 450mm; rear W 450mm x H 250mm.

GIRA

Camera module Gira System 106 - 5561 000, installed without wiring

- A high-quality camera with high light sensitivity is concealed behind the replaceable black glass pane. Thanks to a detection angle of 100°, the user is always in the picture about what is happening outside his front door.

Info module Gira System 106 - 5560 920, installed

- For house numbers that need to be clearly visible.

Door station module Gira System 106 - 5565 920, installed without wiring

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with voltage via the door station module.

Home station Gira video surface-mounted 7 1209xx, enclosed

- Video home station with a 17.78 cm (7") TFT color display and convenient hands-free function for surface mounting or wall mounting with flush-mounted device box or cavity wall box. With the optional stand (see accessories) also suitable for placement on furniture. A 32 GB SD memory card is included for internal image storage. Full-surface glass front with touch functionality and tactile feedback.

• [Further information](#)

Control device video REG Gira 128800, enclosed

- Control device for supplying the audio and video components of the Gira door communication bus.
- Supply of the reverse polarity protected and short-circuit proof 2-wire bus when using video components such as color camera, TFT color display.
- Up to 2 door stations with color camera and 28 home stations with TFT color display can be supplied via the video control device.
- A total of up to 15 color cameras can be controlled by the video control device (5 door stations video and 10 TKS camera gateways), of which two door stations with color camera can be supplied with voltage by the video control device. The other color cameras must each be operated with their own power supply for door communication.
- Self-resetting electronic short-circuit and overload detection of the operating voltages and the bus connection.
- Buttons for system and door opener programming.
- LED status indicators for operation, overload, system programming and door strike programming.
- AC 12 V output for powering a standard electric strike.
- Relay output for switching a door opener with its own power supply.
- Door opener switching time continuously adjustable from 1 to 10 s.
- [Further information](#)

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your local electrician for planning, installation and wiring.

Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy.

Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. This system is protected against water ingress in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Back
Base material:	Stainless steel
Connection technology:	2-wire bus technology
Height single box in cm:	20,0
Width single box in cm:	40,0
Volume single box in liters:	24,0 - 32,0 32,0 - 44,0
Height letter slot in cm:	3,5
Width letter slot in cm:	36,0
Total width in cm:	45,0
Depth in cm:	BK 30,0 - 39,0 BK 39,0 - 56,0 FK 10,0
Weight in kg:	21,0
Delivery condition:	Delivery is partially disassembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).