



**Order number:** 611-4363L

**Manufacturer:** elo

ab **€1,869.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

## elo 43 inch Open Frame Touchscreen

Elo's 4363L 43-inch full-HD open frame enables easy integration into enclosures and kiosks with its state-of-the-art slim format. Whether for self-order and self-checkout kiosks or industrial control panels, plant room control panels, and wayfinding solutions, Elo's commercial-grade interactive displays offer the versatility to add touch capabilities to your solution.

Designed for easy integration: mount the 4363L touchscreen monitor in landscape, portrait, or prone formats for optimal flexibility in integrating with any counter, kiosk, or cabinet design.

Place your touchscreen behind an extra layer of protection: For installations that require specific IP ratings or protection from vandalism and demanding environments, Elo TouchPro PCAP displays offer superior touch response with capacitive reactance.

Touch response with capacitive reactance allows the display to be mounted behind a glass front up to 6 mm thick or a plastic front up to 3 mm thick to create a fully enclosed kiosk.

Brilliant, interactive TouchPro® PCAP display: the 63 Series offers anti-glare or anti-friction models with borderless glass and up to 40 simultaneous touches for an enhanced tablet-like experience.

### Specifications

<b>Case color:</b>	Black
<b>Contrast ratio:</b>	4000:1
<b>Screen diagonal:</b>	42.5 inch diagonal, active-matrix TFT LCD (LED)
<b>Active area:</b>	37.04" x 20.84" / 940.86 mm x 529.254 mm
<b>Surface treatment:</b>	Anti-friction
<b>Touch user interface:</b>	USB
<b>Bezel:</b>	Without bezel
<b>Brightness (typical):</b>	LCD panel: 450 cd/m <sup>2</sup>   TouchPro PCAP: 387 cd/m <sup>2</sup>
<b>Colors:</b>	8-bit (16.7 million)
<b>Resolution:</b>	1920 x 1080 @ 60hz
<b>Total response time (typical):</b>	8 msec
<b>Input voltage:</b>	100-240 VAC, 50/60 Hz
<b>Power consumption (typical):</b>	ON (monitor + AC/DC adapter): 51 W   Hibernation (monitor + AC/DC adapter): 0.61 W   OFF (monitor + AC/DC adapter): 0.20 W
<b>Operating temperature:</b>	Portrait/landscape: 0°C to 40°C / 32°F to 104°F   Desktop: 0° C to 35° C / 32°F to 95°F
<b>Storage temperature:</b>	Portrait/landscape: -20°C to 60°C / -4°F to 140°F   As tabletop unit -20° C to 60° C / -4° F to 140° F
<b>Humidity:</b>	Operating: 20% to 80%   Storage: 10% to 90% (38.7° max wet bulb thermometer temperature)
<b>MTBF:</b>	50.000 hours, verified

### Abmessungen & Details

<b>Screen orientation:</b>	Landscape, Portrait
<b>Interfaces:</b>	USB, RJ45, HDMI, VGA
<b>Height in cm:</b>	58,75
<b>Width in cm:</b>	99,93
<b>Depth in cm:</b>	6,62
<b>Weight in kg:</b>	10,2

**Shipping information:** Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).