





Order number: 385-7016VA-1-SP

Manufacturer: Briefkasten Manufaktur Lippe

ab **€549.00** *

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users

with VAT ID and Non-EU countries)





1er free-standing letterbox Design BASIC 385 ST-R with bell box - stainless steel RAL 7016 anthracite gray

Modern free-standing letterbox made in Germany by Briefkasten Manufaktur.

The letterboxes are made of galvanized steel, powder coated in anthracite gray RAL 7016, the stand elements are made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, an insertion flap with rubber lip, the solid changeable name plate and the robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

- free-standing letterbox made of galvanized steel, powder coated in anthracite gray RAL 7016
- The system is made at the letterbox manufactory. German quality production "Made in Germany".
- The letterbox complies with DIN/EN 13724. Throw-in size (3.5 cm x 26.5 cm) for C4 crosswise, large letters fit in here without bending.
- · Stainless steel flap, polished with noise-dampening rubber lip for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number and change name plate under the access flap.
- Optionally with close-fitting side paneling + rain canopy made of stainless steel V2A, powder coated in RAL 7016 anthracite gray fine structure matt.
- The stand elements are made of 60.0 mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.
- Speech-bell part made of galvanized steel, powder coated in anthracite-grey RAL 7016
- Speech perforation with universal adapter. (Intercom system/built-in loudspeaker not included).
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- · Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.

Important information:

Mail is protected from moisture and dirt only when fully inserted and flap closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Steel galvanized, Stainless steel
Height single box in cm:	11,0
Width single box in cm:	30,0
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm:	: 22,0
Width letterbox system in cm:	30,0
Overall height in cm:	120,0 150,0 170,0
Total width in cm:	46,5
Depth in cm:	43,5
Weight in kg:	16,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).