

Order number: 1245-SLINE-SET-B

Manufacturer: ekey



ab **€771.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



ekey sLine fingerprint set

The ekey sLine fingerprint set is a biometric access solution that provides keyless access to buildings using intuitive touch operation. Thanks to its shallow installation depth, the fingerprint can be installed in intercom systems and cavities (e.g. letterboxes). The set includes the ekey sLine fingerprint and the ekey Controller REG. The system is administered via the ekey bionyx app.

Free range of functions

- Intuitive administration with smartphone
- Opening with fingerprint
- Number of users: 20 (more users on request)
- Access log (activate/deactivate and delete)
- Remote opening
- Push messages when the door is opened
- Amazon Alexa connection
- Smart home connectivity (HTTP(S) requests, APPMODULE, REST-API)
- Firmware updates
- Remote management of authorizations
- User and role management
- Data backup of the device configuration
- Finger synchronization to other devices
- Up to 5 fingerprints in one system
- Remote support
- Simple device replacement
- Different functions with different fingers (device-dependent)
- COMING SOON time window (e.g. person X: access Wednesday, 09:00 to 13:00)

Operating data

- Type of supply: DC
- Supply nominal voltage max: 30 V
- Supply rated voltage min: 10 V
- Supply nominal voltage nominal operation: 24 V
- Current consumption max: 17 mA
- Current consumption min: 14 mA
- Current consumption rated operation: 16 mA
- Power max: 0.4 W
- Power min: 0.3 W
- Power rated operation: 0.4 W
- Operating temperature min: -25 °C
- Operating temperature max: 70 °C
- Humidity max: 90 %rel
- Protection class: IP54
- Suitable for unprotected outdoor areas: Yes
- Suitable for protected outdoor areas: Yes
- FAR: 1:10 000 000
- FRR: 1:100
- Nominal voltage tolerance: 10%
- Signaling: Optical | Acoustic

Mechanical data

- Design: sLine
- Mounting type: in the intercom system
- Mounting height min: 105 cm
- Width: 66 mm
- Length/height: 66 mm
- Depth: 32 mm
- Material: ASA plastic
- Surface: Plastic
- UV-resistant: Yes

Bluetooth communication

- Bluetooth standard: 4.2
- Bluetooth class: Class 1
- Range type: 10 m

Abmessungen & Details

Weight in kg: 0, 30

Delivery condition: Components individually (we recommend assembly by an electrician)

Shipping information: Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).