



# 2-compartment Stainless steel free-standing letterbox BASIC Plus 592C ST-P powder coated - Bell box - INDIVIDUAL

This 2-compartment mailbox system combines the highest quality and modern design. The system is completely made of stainless steel V2 A 1.4301, powder coated in RAL color. The grinding pattern captivates by the charisma of highest elegance. Extremely high quality workmanship and the sophisticated concept make this 2-compartment free-standing letterbox our top seller. A rain drainage edge for optimal water protection, rubber buffers for quiet insertion and the very robust change name plate distinguish this free-standing letterbox.

The elegant rectangular columns are solidly manufactured from 2 mm stainless steel V2A 1.4301, powder coated in RAL color and optionally equipped with a 10mm thick base plate for screw mounting.

Thanks to the construction method, self-assembly is uncomplicated.

The letterbox system is created by the letterbox manufactory. 100% Made in Germany, Bad Salzuflen.

- free-standing letterbox system for 2 parties with letterboxes made of stainless steel V2A 1.4301, powder coated in RAL color.
- The withdrawal doors can be opened from left to right with rain drainage edge for optimal water protection.
- Insertion flap with noise-damping rubber buffers for very quiet insertion of mail.
- With changeable name plate and 2 keys per individual mailbox.
- The mailboxes comply with DIN EN 13724. Insertion size (3.5 cm x 32.5 cm) for DIN C4 landscape, here also large letters fit without bending.
- The pillars are made of W 20 mm x D 100 mm stainless steel V2A 1.4301, ground for setting in concrete or for screw mounting.
- Incl. close-fitting side cladding+rain roof made of stainless steel V2A, powder-coated in RAL color.
- · Bell intercom unit for 2 rental parties made of 2mm stainless steel V2A 1.4301, powder coated in RAL color
- Dimensions intercom & bell unit: W 170 mm x H 660 mm x D 100 mm. Optionally also mounted on the left side. Please specify.
- 2x bell push buttons, round, stainless steel, max. 24 V AC/DC, 1.5 A, IP 54.
- The inscriptions of the name plates can be exchanged as desired .
- · Optionally with house number, white illuminated.
- Preparation (built-in speaker not included) for intercom possible.
- Optional with universal adapter for all commercially available built-in speakers.
- Optional preparation (camera not included) for a camera.
- Invisible cable feed through the stand elements possible.

### Important information

#### Camera or speaker preparation

## We recommend that the electrical installation is always carried out by an electrical installer.

We offer the preparation of cameras & intercoms of different manufacturers for our mailboxes. The preparation does not include terminal equipment, it is the provision of the screw mounts, holes & perforations. So that you can mount your terminal device without any problems.

## Water protection

In order to achieve optimal water protection for your mail, the mailbox or mailbox system should be located under a canopy if possible. Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

## **Abmessungen & Details**

Number of parties:	2
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Overall height in cm:	140,0   160,0
Total width in cm:	60,5
Depth in cm:	10,0
Weight in kg:	32,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the

stand & box can be shipped separately).