



Datasheet for Design letterbox pedestal GOETHE 1200 - RAL of your choice

Order number: 215-STL-120 Manufacturer: Briefkasten Manufaktur Lippe

ab **€2,401.00** *

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Briefkasten Manufaktur® Lippe GmbH

Datasheet for Design letterbox pedestal GOETHE 1200 - RAL of your choice



Briefkasten Manufaktur[®] Lippe GmbH

Design letterbox pedestal GOETHE 1200 - RAL of your choice

The modern GOETHE letterbox pedestal is ideal for the sophisticated entrance area. The linear design without a visible lock makes this letterbox look particularly elegant.

The dimensions of the single box allow a capacity of approx. 16 liters, the large insertion guarantees no crumpled mail even with DIN C4 envelopes and magazines or after several days of absence. The innovative push-key lock is concealed inside the letterbox. The key is simply inserted into the existing opening (no turning necessary) and the door opens. With the arrangement of the lock, this letterbox is designed in such a way that the removal door prevents the mail from falling towards you. The water drainage edge ensures that the mail inside is optimally protected from the weather. The insertion flap is fitted with high-quality axle dampers, guaranteeing quiet closing and preventing annoying rattling caused by the weather.

The letterbox systems in the GOETHE collection are characterized by the consistent use of stainless steel and aluminium. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are available directly in our store.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5

- High-quality letterbox pillar made of stainless steel and aluminum.
- Quality production Made in Germany by Briefkasten Manufaktur Lippe.

• Letterbox (BH 400x400mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice.

· Innovative push-key lock with 2 keys.

• Letter insertion and removal from the front. Insertion flap with high-quality axle dampers for very quiet mail insertion.

• The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 across, even large letters fit in here without creasing.

- Removal door opens from top to bottom. So the mail cannot fall towards you.
- Functional box (BH 400x400mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice with stainless steel laser inscription or illuminated inscription.

• Optimum rain protection thanks to rain guard edges and a rain roof made of 3mm aluminum AIMg3 W19, powder-coated in RAL of your choice.

- Side cladding made of 3mm aluminum AIMg3 W19, powder-coated in RAL of your choice.
- Rear panel and base plate made of 6mm aluminum AIMg3 W19, powder-coated in RAL of your choice.
- Invisible fastening in the pillar thanks to reinforced base plate. The overall height is 1.22 m.

Important information

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible. The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel, Aluminum
Height single box in cm:	BK 40.0
Width single box in cm:	40,0
Volume single box in liters	: BK 16.0
Height letter slot in cm:	3,5
Width letter slot in cm:	36,0
Overall height in cm:	121,7
Total width in cm:	40,8
Depth in cm:	10.0 + 2.5 Rain roof
Weight in kg:	32,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.