



**Order number:** 382A-7016-6-SP-100-O

**Manufacturer:** Briefkasten Manufaktur Lippe

ab **€1,243.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users  
with VAT ID and Non-EU countries)



### 6-compartment Surface mount mailbox Design BASIC 382A AP with bell box - RAL 7016 anthracite gray

High quality stainless steel surface mailbox for 6 parties made in Germany by Briefkasten Manufaktur.

The complete surface mailbox system is made of galvanized steel, powder coated in RAL 7016 anthracite gray. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimum water protection, a double-edged access flap with rubber buffer, the solid changeable name plate, a practical mail holding bracket and the very robust lock characterize this surface-mounted mailbox system.

Thanks to the construction method, self-assembly is uncomplicated. The mailbox system is prepared for uncomplicated complete assembly, here no complex wall mounting of individual boxes must take place.

#### • 6-compartment Surface-mounted mailbox made of galvanized steel, powder-coated in RAL 7016 anthracite gray

- The system is made at the letterbox manufactory. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber buffers for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.
- Additional rain protection is provided by the optional rain protection roof, flush at the back and protruding to the front, made of stainless steel V2A, powder-coated in RAL anthracite gray 7016 fine structure.
- For wall mounting incl. fixing material (screws + dowels). For fence mounting also available without rear perforation (perforation must be provided by customer).
- **Speech bell part made of galvanized steel, powder-coated in RAL 7016 anthracite gray**
- Speech perforation with universal adapter. (Intercom system/built-in loudspeaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritzo, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 6x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1,5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.

#### Optional components



The COMELIT video intercom sets are completely pre-wired and programmed by us, so the set is ready for connection. Only 2 wires to connect!

The intercom sets from COMELIT are simply connected with the 2-wire technology. This means that the existing lines can be used and there are no additional costs for laying new lines and plastering or painting work. From the new power supply unit in the meter cabinet, simply lay 2 wires to the built-in loudspeaker in the function box of the letterbox system, as well as 2 wires from the power supply unit to the door station in the apartment. DONE.

- ++ ideal for conversion and renovation, as existing bell lines can be used
- ++ no additional effort for plastering and painting
- ++ low costs due to simple installation
- ++ simple commissioning
- ++ including handicap function at the door
- ++ can be expanded at any time to include handicap-suitable monitors for hearing aid users

#### Face recognition and voice commands

Integration with Amazon Alexa, available for free via Mini Wi-Fi, is the incredible innovation that led to the creation of the first voice-controlled video intercom. This can also be activated remotely. We already know that with a glance, the phone can be unlocked. Why shouldn't it also be possible to open the gate to the house? Comelit is fully exploiting the potential of the cloud and is the first company in Germany to offer the new facial recognition function: an intuitive and very useful way to manage access to your home via the video intercom.

#### The functions

- Receive calls from the door station wherever you are.
- To view the recordings of the cameras of your installation (including cameras of the door station).
- To retrieve the video messages of visitors recorded during your absence.
- To call the internal devices of your system (indoor audio and video intercoms).
- To open gates, doors and turn on the lights.
- The APP is based on PUSH notifications; this means considerable energy and data savings, as the APP is only activated when a call is received, and much more.

#### Video intercom set

##### • 6741W door station with mobile function

Color monitor with 4.3" 16/9 screen, hands-free full-duplex and touch-sensitive buttons. Allows brightness, contrast control and adjustment of the strength of the audio signal and ring tone. There are several melodies to choose from to personalize the ringtone. Standard equipment with buttons for door opener, for activation/deactivation of voice connection with corresponding LED indicators. Door station with Wifi interface for simulation of domestic Presence: in combination with the COMELIT app, door calls can be answered from anywhere and doors and gates can be opened. Face recognition for contactless access is possible with the COMELIT app. Dimensions: 160 x 115 x 22 mm (WHT).

##### • Video speaker 4681 with holder 1250U switch

Color audio-video unit for 2-wire system, complete with front adjustable LED illuminated color camera. Equipped with terminal block, speech connection with echo cancellation, dustproof and waterproof loudspeaker, electret microphone and loudspeaker volume adjustable at the front. Additional visual and audible programmable handicap indicators. Integrated electronic door opener function (3 A) and additional relay contacts C, NC, NO with 10 A. Dimensions: 102 x 55 x 38 mm (WHT)

##### • 2-wire power supply unit 1210

Power supply unit with toroidal transformer, overload and short-circuit protection for the 2-wire system (SB2) for supplying the landing station (L1-L1) and the riser (L2-L2). Equipped with a terminal for line termination art. 1216. Input voltage 110-240V AC. Dimensions: 8 DIN modules.

#### Important information

##### Camera or intercom preparation

Intercom systems must be connected by an electrician. Contact your trusted electrician for design, installation and wiring.

##### Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

#### Abmessungen & Details

Number of parties:	6
Item withdrawal:	Front
Base material:	Steel galvanized
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0   17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	109,0
Width letterbox system in cm:	71,0
Depth in cm:	10,0   15,0
Weight in kg:	42,0
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).