



**Order number:** 311X-6-R-VA-R-100

**Manufacturer:** Briefkasten Manufaktur Lippe

ab **€2,925.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



## 6-compartment free-standing letterbox BASIC 311X ST-R with bell box - stainless steel insertion - RAL of your choice

The letterboxes are made of stainless steel V2A, powder-coated in RAL color, the stand elements and insertion flap are made of weather-resistant stainless steel V2A, polished. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimum water protection, a double-edged access flap with rubber buffer, the solid changeable name plate, a practical mail holding bracket and the very robust lock are the distinguishing features of this free-standing letterbox. This mailbox is easy to clean and insensitive. This system is additionally equipped with a very high-quality bell intercom unit made of stainless steel V2A, ground. The bell intercom unit is delivered optionally with prepared intercom and/or camera. A quality product made in Germany.

### • 6 parties stainless steel mailbox system with mailboxes made of stainless steel V2A, powder coated in RAL color

- Ideal for apartment buildings.
- Incl. rain protection roof made of stainless steel.
- Insertion flaps made of stainless steel V2A, ground with noise-damping rubber buffers for very quiet insertion of mail.
- Doors open from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- The boxes comply with DIN/EN. Insert C4 crosswise, here fit even large letters without bending.

### • Bell-intercom part for 6 rental parties made of stainless steel V2A, polished

- Dimensions: W 190mm x H approx 400mm (may vary, depending on installation parts) x T 60mm.
- Optionally mounted on the left or right side.
- Optionally with house number in polished optics (67mm high).
- 8-12V DC short stroke bell push button with LED ring illumination (blue, white, red or green). The illumination of the bell push button cannot be supplied by the control unit. It must be connected to an additional 8-12V DC power supply.
- Optionally, an 8-12V DC short-stroke light button with pictogram is possible.
- The inscriptions of the nameplates can be exchanged as desired.
- Preparation (built-in loudspeaker not included) for intercom system possible.
- Optional universal adapter for all commercially available built-in loudspeakers.
- Optional preparation (camera not included) for a camera.
- The pedestals are made of 42.4 mm stainless steel V2A, ground. Invisible cable routing through stand elements.

## Important information

### Camera or microphone unit preparation

**We recommend that the electrical installation is always done by an electrician.**

We offer the preparation of cameras & intercoms of different manufacturers for our mailboxes. The preparation does not include terminal equipment, it is the provision of the screw mounts, holes & perforations. So that you can mount your terminal device without any problems.

### Water protection

In order to achieve optimal water protection for your mail, the mailbox or mailbox system should be located under a canopy if possible. Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

## Abmessungen & Details

Number of parties:	6
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0   17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	99,0
Width letterbox system in cm:	71,0
Overall height in cm:	150.0 + 7.0 attached rain roof
Total width in cm:	121,0
Depth in cm:	10,0   15,0
Weight in kg:	48,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).