



Order number: 384Q-VA-1-SP-100-O

Manufacturer: Briefkasten Manufaktur Lippe

ab **€537.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Stainless steel free-standing letterbox Design BASIC 384 ST-Q with bell box

High-quality stainless steel free-standing letterbox made in Germany by Briefkasten Manufaktur.

The complete mailbox system is made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this stainless steel mailbox system our top seller. A rain drainage edge for optimum water protection, a double-edged insertion flap with rubber buffer, the solid change name plate, a practical mail holding bracket and the very robust lock characterize this stainless steel letterbox system.

Thanks to the construction method, self-assembly is uncomplicated.

• free-standing letterbox made of weatherproof V2A stainless steel 1.4301, grinded

- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- The letterbox complies with DIN/EN 13724. Throw-in size (3.5 cm x 32.5 cm) for C4 crosswise, large letters also fit in here without bending.
- Insertion flap with noise-dampening rubber buffers for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- Optional newspaper compartment, rear side, open on both sides made of V2A stainless steel 1.4301, ground.
- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.
- Additional rain protection is achieved by the optional rain protection roof made of stainless steel V2A, polished.

• Speech-bell part made of weatherproof V2A stainless steel 1.4301, grinded

- Speech hole with universal adapter. (Intercom system / built-in speaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.
- The stand elements are made of 40x40mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, installation and wiring.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	43,0
Width letterbox system in cm:	35,5
Overall height in cm:	120,0 150,0
Total width in cm:	43,5
Depth in cm:	10,0 15,0
Weight in kg:	15,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).