



# 1 stainless steel free-standing letterbox Design BASIC Plus 385 220 ST R with bell box

Modern free-standing letterbox for 1 party made in Germany by Briefkasten Manufaktur.

The letterboxes and the stand elements are made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, an insertion flap with rubber lip, the solid changeable name plate and the robust lock distinguish this free-standing letterbox. This letterbox is easy to clean and insensitive.

The letterboxes of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The construction has been developed by our own engineers with regard to high flexibility resp. modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus units.

- 1er free-standing letterbox made of stainless steel V2A, grinded
- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flap with noise-damping rubber lip for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number and change name plate under the access flap.
- Incl. close-fitting side panel + rain cover made of stainless steel V2A, ground.
- The stand elements are made of 60.0 mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.
- · Speech-bell part made of stainless steel V2A, grinded.
- · Speech hole with universal adapter. (Intercom system/built-in loudspeaker not included).
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- · Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.

#### Important information

#### Camera or intercom preparation

Intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

## Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

### **Abmessungen & Details**

•	
Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	22,0
Width single box in cm:	30,0
Volume single box in liters:	25,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm:	33,0
Width letterbox system in cm:	30,0
Overall height in cm:	120,0   150,0   170,0
Total width in cm:	46,5
Depth in cm:	43,5
Weight in kg:	16,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).