



Order number: 863-ST-1-SP-7016

Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,359.00** *

incl. VAT $\underline{\text{plus shipping costs}}$ (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Briefkasten Manufaktur® Lippe GmbH





Parcel post box freestanding BASIC 863 ST-R with bell box & parcel compartment 550x370 in RAL 7016 anthracite gray

Parcel reception independent of the delivery company! Every parcel deliverer (e.g. DHL, DPD, TNT, GLS, Hermes, etc.) can use this parcel mailbox. Sample garage contracts enclosed!

The mailbox is made of galvanized steel, powder coated in anthracite-gray RAL 7016, the standing elements are made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, a throw-in flap with rubber lip, the solid changeable name plate and the robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive. Thanks to the construction method, self-assembly is uncomplicated.

Parcel post box / letter box system made of galvanized sheet steel, powder coated in RAL 7016 anthracite gray fine structure matt

- Parcel compartment 370x550x380 mm (WHT) incl. parcel lock with snap-in lock.
- Volume parcel compartment: 77 liters, Max. Package size: 340 x 520 x 350 mm (WHT).
- Parcel box door with three-point locking including a door reinforcement.
- Door incl. through-engraving with stainless steel backing, text: "PAKET" vertically aligned, height of lettering approx. 250 mm.
- With horizontal letterbox (WHT 370x110x380mm). Removal from the front, the removal door can be opened from left to right.
- DIN EN 13724 compliant.
- Insertion C4 crosswise from the front, here fit also large letters without bending. Insertion flap with sound-absorbing rubber seal.
- · With nameplate and 2 keys per individual mailbox.
- The inscriptions of the name plate can be exchanged as desired.
- Close-fitting side panel + rain cover made of 2 mm stainless steel V2A 1.4301, powder-coated. With integrated rain edge protruding to the front, roof plate folded over side plates.
- · Bell box made of stainless steel, powder coated in RAL 7016 anthracite gray
- Intercom perforation with universal adapter. (Intercom system/built-in loudspeaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 1x round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- · Anti-vandalism the nameplates are dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 14 mm (lateral right). Invisible cable routing through the stand element.
- The stand elements are made of 60.0 mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Steel galvanized, Stainless steel
Height single box in cm:	BK 11.0 PK 55.0
Width single box in cm:	BK 37.0 PK 37.0
Volume single box in liters:	BK 15.0 PK 77.0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	: 77,7
Width letterbox system in cm:	38,0
Overall height in cm:	120,0 150,0
Total width in cm:	53,0
Depth in cm:	39,0
Weight in kg:	40,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.