# Briefkasten Manufaktur® Lippe GmbH



Briefkasten Manufaktur<sup>®</sup> Lippe GmbH

### 6-compartment free-standing letterbox Design BASIC 385-9016 ST-R with bell box - RAL 9016 traffic white

Modern free-standing letterbox for 6 parties made in Germany by Briefkasten Manufaktur.

The mailboxes are made of galvanized steel, powder-coated in RAL 9016 traffic white, the stand elements are made of weatherresistant stainless steel V2A, polished. The very high quality workmanship and the well thought-out concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, an insertion flap with rubber lip, the solid changeable name plate and the robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive. Thanks to the construction method, self-assembly is uncomplicated.

## 6-compartment free-standing letterbox made of galvanized steel, powder coated in RAL 9016 traffic white fine structure matt

- The system is made at the letterbox manufactory. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 high, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number and changeable name plate under the access flap per mailbox.

• Optionally with close-fitting side panel + rain cover made of stainless steel V2A, powder coated in RAL 9016 traffic white fine structure matt.

- The stand elements are made of 60.0 mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.
- · Speech bell part made of galvanized steel, powder-coated in RAL 9016 traffic white fine structure matt.
- Speech perforation with universal adapter. (Intercom system/built-in speaker not included).

• Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.

#### Important information:

Mail is protected from moisture and dirt only when fully inserted and flap closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

### **Abmessungen & Details**

Number of parties:	6
Item withdrawal:	Front
Base material:	Steel, galvanized
Height single box in cm:	11,0
Width single box in cm:	30,0
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm	: 44,0
Width letterbox system in cm:	60,0
Overall height in cm:	120,0   150,0   170,0
Total width in cm:	76,5
Depth in cm:	43,5
Weight in kg:	47,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).