




Order number: 385A-9016-5-SP

Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,199.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



5-compartment Surface mounted letterbox system Design BASIC 385A-9016 AP with bell box - RAL 9016 traffic white

Modern surface mounted mailbox system for 5 parties made in Germany by Briefkasten Manufaktur.

The mailboxes are made of galvanized steel, powder coated in RAL 9016 traffic white. A close-fitting side panel with rain cover and the rain gutters for optimal water protection, a throw-in flap with rubber lip, the solid changeable name plate and the robust lock distinguish this mailbox system. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

• **5-compartment Surface-mounted mailbox system completely powder-coated in RAL 9016 traffic white fine structure matte**

- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- The mailboxes are made of galvanized steel, powder coated in RAL 9016 traffic white fine structure matt and comply with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 high, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number and change name plate under the access flap per mailbox.
- Incl. close-fitting side panel+rain cover made of stainless steel V2A, powder-coated in RAL 9016 traffic white fine structure matt.
- Incl. mounting material for wall mounting.
- **Speech bell part made of galvanized steel, powder-coated in RAL 9016 traffic white fine structure matt.**
- Speech perforation with universal adapter. (Intercom system/built-in speaker not included).
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is dent and impact resistant, the plastic is flame retardant.

Important information:

Mail is protected from moisture and contamination only when fully inserted and the flap is closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	5
Item withdrawal:	Front
Base material:	Steel galvanized, Stainless steel
Height single box in cm:	11,0
Width single box in cm:	30,0
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm:	77,0
Width letterbox system in cm:	30,0
Depth in cm:	43,5
Weight in kg:	35,0
Delivery condition:	Delivery is completely assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).