





Order number: 385KXA-4-SP

Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,558.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users
with VAT ID and Non-EU countries)



4-compartment Surface mount mailbox BASIC Plus 385KXA AP with bell box - camera preparation

Modern surface mailbox for 4 parties made in Germany by Briefkasten Manufaktur.

The mailboxes are made of stainless steel V2A, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A close-fitting side panel with rain cover and the rain gutters for optimal water protection, an insertion flap with rubber lip, the solid interchangeable name plate and the robust lock distinguish this mailbox system.

Thanks to the construction method, self-assembly is uncomplicated.

- **4-compartment Surface-mounted mailbox made of stainless steel V2A, powder-coated in RAL color**

- The system is made at the letterbox manufactory. German quality production "Made in Germany".

- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 crosswise, here fit even large letters without bending.

- Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.

- The doors can be opened from left to right.

- Incl. 2 keys with key number and changeable name plate (type 2) under the access flap.

- Incl. close-fitting side panel + rain roof made of stainless steel V2A, powder-coated in RAL color.

- **Bell box made of stainless steel V2A, powder coated in RAL color**

- Preparation (built-in loudspeaker not included) for intercom possible. Optional with universal adapter for all commercially available built-in speakers.

- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).

- Anti-vandalism - the nameplate (type 1) is dent-proof and impact-resistant, the plastic is flame-retardant.

- Preparation (camera not included) for a camera.

- Incl. mounting material for wall mounting.

Important information:

Mail is protected from moisture and dirt only when fully inserted and flap closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	4
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	11,0
Width single box in cm:	30,0
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm:	66,0
Width letterbox system in cm:	30,0
Depth in cm:	43,5
Weight in kg:	20,0
Delivery condition:	Delivery is completely assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).