



Order number: 529-KSDB2100E-6-UP-VA Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,799.00** \*

incl. VAT  $\underline{\text{plus shipping costs}}$  (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)











# Stainless steel door station BASIC 529 with DoorBird D2100E video intercom - VIDEO set for 6 parties

This simple and elegant doorbell plate fits seamlessly into the house facade. Manufactured in 2mm brushed V2A stainless steel. Integrated DoorBird IP video door station D2100E. The DoorBird IP Video Door Station D2100E is the smart solution for your front door. The IP Video Door Station can be operated as a standalone unit or integrated into an existing smart home platform. Even existing, classic installations such as a door chime or an electric door and gate opener can continue to be used with DoorBird and controlled via the app.

Our products have a high value, reliable functionality and their own identity. Made by Briefkasten Manufaktur. DoorBird was also not only invented and developed in Germany, but is also produced in Berlin to this day. At DoorBird, "Made in Germany" is not just a seal, but a lived philosophy. The IP video door stations are manufactured in the DoorBird manufactory to guarantee the highest quality, durability and customer satisfaction.

The delivery includes the matching flush-mounted box for easy installation.

- Door station made of 2 mm stainless steel V2A 1.4301, 240 grain ground or powder coated in RAL fine structure matt.
- Dimension of bell plate W 160 mm x H 350 mm.
- The body has the dimensions: W 130 mm x H 320 mm x D 50 mm.
- Incl. 4x screws cover caps made of stainless steel V2A, ground, so that the screws for fixing the front panel are not visible. See pictures.
- Incl. wall flush-mounted box made of galvanized steel.
- Flush mount box with moss rubber gasket on the back and pre-cut cable inlets on the side & back panel.
- Incl. DoorBird IP video door station D2100E installed.

### Important information

### Camera or intercom preparation

Intercom systems must be connected by an electrical contractor. Contact your trusted electrical contractor for planning, installation and setup.

#### Water protection

For optimum water protection, the door station should be located under a canopy if possible.

## **Abmessungen & Details**

Number of parties: 6

Base material: Stainless steel

Connection technology: LAN Number of bell buttons: 6

**Height in cm:** 44,0 | 41,0 **Width in cm:** 16,0 | 13,0

Depth in cm: 5,0 Weight in kg: 8,0

**Delivery condition:** Delivery is assembled

Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial

**Shipping information:** deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand

& box can be shipped separately).