



## Bell pillar designer - stainless steel V2A powder coated - 4 party - INDIVIDUAL

High quality manufactured bell pillar for 4 parties completely made of stainless steel V2A, powder coated of the brand Briefkasten Manufaktur. This bell pillar is available with 1-6 bell buttons. Wahleise can be prepared a speech hole, camera and house number. Our products have high quality, reliable functionality and their own identity. Made by Mailbox Manufacture.

- Bell pillar made of 1.5 mm stainless steel V2A 1.4301, powder coated.
- The system is made by Briefkasten Manufaktur. German quality production "Made in Germany".
- The speaking part is made of 2mm stainless steel V2A 1.4301, powder coated. Dimensions: W 190 mm x H 640 mm x D 110 mm.
- House number approx. 70mm high (max. 3 digits) with power-saving LED illumination 12V DC approx. 50mA / 1W, white.
- Exchangeable nameplate made of plexiglass, optionally illuminated.
- The inscriptions of the name plates can be exchanged from the front as desired.
- Incl. EVN LED power supply / transformer IP65 12V/DC 0.1-4W for the LED lighting (house number and nameplate if selected).
- 4x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1,5 A, IP 54 (pressure force limitation).
- Preparation (built-in speaker not included) for intercom possible.
- Optional universal adapter for all commercially available built-in speakers.
- Optional preparation (camera not included) for a camera.
- Incl. 6x screws cover caps made of stainless steel V2A, ground, so that the screws for fixing the front panel are not visible. See pictures.
- The fully welded column is made of 1,5mm stainless steel V2A 1.4301, powder coated. Construction height is either 1.30 m or 1.60 m.
- The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. See pictures.
- Invisible cable feed through the body is possible.

### Important information

#### Water protection

In order to achieve optimal water protection for your mail, the mailbox or mailbox system should be located under a canopy if possible.

Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1cm). This is not a reason for complaint.

### Abmessungen & Details

<b>Number of parties:</b>	4
<b>Base material:</b>	Stainless steel
<b>Height single box in cm:</b>	64,0
<b>Width single box in cm:</b>	19,0
<b>Overall height in cm:</b>	130,0   160,0
<b>Total width in cm:</b>	22.0 (footplate 32.0)
<b>Depth in cm:</b>	11.0 (footplate 21.0)
<b>Weight in kg:</b>	40,0
<b>Delivery condition:</b>	Delivery is assembled
<b>Shipping information:</b>	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.