



## 1er bell pillar designer - stainless steel V2A powder coated with DoorBird video intercom system

High-quality manufactured bell pillar completely made of stainless steel V2A, powder-coated of the brand Briefkasten Manufaktur. Integrated DoorBird IP video door station D2100E or D1100E. The DoorBird IP Video Door Station D2100E or D1100E is the smart solution for your entrance door. The IP Video Door Station can be operated as a stand-alone unit or integrated into an existing smart home platform. Even existing, classic installations such as a door chime or an electric door and gate opener can continue to be used with DoorBird and controlled via the app.

Our products have a high value, reliable functionality and their own identity. Made by Briefkasten Manufaktur. The DoorBird was also not only invented and developed in Germany, but is also produced in Berlin to this day. At DoorBird, "Made in Germany" is not just a seal, but a lived philosophy. The IP video door stations are manufactured in the DoorBird factory to guarantee the highest quality, durability and customer satisfaction.

- Bell pillar made of 1.5 mm stainless steel V2A 1.4301, powder coated.
- The system is made at the mailbox manufactory. German quality production "Made in Germany".
- The speaking part is made of 2mm stainless steel V2A 1.4301, powder coated. Dimensions: W 190 mm x H 640 mm x D 110 mm.
- House number approx. 70mm high (max. 3 digits) with power-saving LED lighting 12V DC approx. 50mA / 1W, white.
- Incl. 6x screws cover caps made of stainless steel V2A, ground, so that the screws for fixing the front panel are not visible. See pictures.
- The fully welded stand column is made of 1.5mm stainless steel V2A 1.4301, powder coated. Construction height is either 1.30 m or 1.60 m.
- The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. See pictures.
- Invisible cable feed through the body is possible.
- Incl. DoorBird IP video door station D2100E or D1100E installed.

### Important information

#### Camera or intercom preparation

**The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.**

#### Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy.

Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1cm). This is not a reason for complaint.

### Abmessungen & Details

<b>Number of parties:</b>	1
<b>Base material:</b>	Stainless steel
<b>Connection technology:</b>	LAN
<b>Height single box in cm:</b>	64,0
<b>Width single box in cm:</b>	19,0
<b>Overall height in cm:</b>	130,0   160,0
<b>Total width in cm:</b>	22.0 (footplate 32.0)
<b>Depth in cm:</b>	11.0 (footplate 21.0)
<b>Weight in kg:</b>	40,0
<b>Delivery condition:</b>	Delivery is assembled
<b>Shipping information:</b>	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.