






Order number: 382XA-3-SP-100-R

Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,231.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



3-compartment 2x2 stainless steel surface mailbox Design BASIC Plus 382XA AP with bell box - RAL of your choice

High quality surface mailbox for 3 parties - made in Germany by Briefkasten Manufaktur.

The complete surface-mounted mailbox system is made of stainless steel V2A, powder-coated in RAL color. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail holding bracket and the very robust lock characterize this surface-mounted mailbox system. The side panel with protruding rain cover made of stainless steel V2A offers optimal protection against the weather and guarantees a very high durability. The high-quality bell panel with stainless steel bell buttons and anti-vandalism nameplates can optionally be equipped with a speech hole for built-in speakers.

The letterbox systems of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The design has been developed by our own engineers with a view to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- 3-compartment Surface-mounted mailbox system with mailboxes made of stainless steel V2A, powder-coated in RAL color.
- The system is made at the Briefkasten Manufaktur. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber seal for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate (type 2) under the access flap and mail holding bracket per mailbox.
- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.
- **Bell box made of weatherproof V2A stainless steel 1.4301, powder coated in RAL color**
- Speech perforation with universal adapter. (Intercom system / built-in speaker not included). Optionally also without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 3x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate (type1) is dent-proof and impact-resistant, the plastic is flame-retardant.
- Incl. side cover + rain cover made of stainless steel V2A, powder coated in RAL color.
- For wall mounting incl. fixing material (screws + dowels).

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

| | |
|---------------------------------------|--|
| Number of parties: | 3 |
| Item withdrawal: | Front |
| Base material: | Stainless steel |
| Height single box in cm: | 33,0 |
| Width single box in cm: | 35,5 |
| Volume single box in liters: | 12,0 17,0 |
| Height letter slot in cm: | 3,5 |
| Width letter slot in cm: | 32,5 |
| Height letterbox system in cm: | 66,0 |
| Width letterbox system in cm: | 71,0 |
| Depth in cm: | 10,0 15,0 |
| Weight in kg: | 24,0 |
| Delivery condition: | Plant is delivered pre-assembled/partially disassembled |
| Shipping information: | Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately). |