



1er free-standing letterbox Design BASIC Plus 380X ST-T with bell box - RAL at choice

High quality free-standing letterbox for 1 party made in Germany by Briefkasten Manufaktur.

The mailboxes are made of stainless steel V2A, powder coated in RAL color, the stand elements are made of aluminum, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail retaining bracket and the very robust lock characterize this free-standing letterbox. This mailbox is easy to clean and insensitive.

The letterboxes of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A and aluminum. The result is a very high durability and sustainability. The design has been developed by our own engineers with a view to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- · 1er free-standing letterbox with letterboxes made of stainless steel V2A, powder-coated in RAL color
- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flap with noise-damping rubber seal for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail retainer.
- Large capacity due to optional mailbox depth +50 mm = approx. 17 I. Suitable for companies and households with very large mail volumes.
- Incl. side cover + rain roof made of stainless steel V2A, powder coated in RAL color.
- · Bell box made of stainless steel V2A, powder coated in RAL color
- Speech perforation with universal adapter. (Intercom system / built-in speaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- · Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 14 mm (lateral right). Invisible cable routing through the stand element.
- The stand elements are made of aluminum profile, powder coated in RAL color for screw mounting or for setting in concrete. **Important information**

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel, Aluminum
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	: 43,0
Width letterbox system in cm:	35,5
Overall height in cm:	120,0 160,0
Total width in cm:	43,5
Depth in cm:	10,0 15,0
Weight in kg:	23,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).