



Order number: 385XA-2-SP

Manufacturer: Briefkasten Manufaktur Lippe

ab **€962.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users
with VAT ID and Non-EU countries)



2-compartment Surface mounted mailbox Design BASIC Plus 385XA AP with bell box - RAL of your choice

Modern surface-mounted mailbox system for 2 parties made in Germany by Briefkasten Manufaktur.

The mailboxes are made of weather-resistant stainless steel V2A, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this mailbox system our top seller. A close-fitting side panel with rain canopy and the rain gutters for optimal water protection, an insertion flap with rubber lip, the solid interchangeable name plate and the robust lock distinguish this letterbox system.

The letterbox systems of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The construction has been developed by our own engineers with regard to high flexibility or modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

• 2-compartment Surface-mounted letterbox system made of stainless steel V2 A, powder-coated in RAL color

- The system is made at the Briefkasten Manufaktur. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 crosswise, here fit even large letters without bending.

- Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.

- The doors can be opened from left to right.

- Incl. 2 keys with key number and change name plate under the access flap.

- Incl. close-fitting side panel + rain roof made of stainless steel V2A, powder-coated in RAL color.

• Bell box made of stainless steel V2 A, powder coated in RAL color

- Intercom perforation with universal adapter. (Intercom system/built-in speaker not included).

- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).

- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.

- Incl. mounting material for wall mounting.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	2
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	11,0
Width single box in cm:	30,0
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	26,5
Height letterbox system in cm:	33,0
Width letterbox system in cm:	30,0
Depth in cm:	43,5
Weight in kg:	12,0
Delivery condition:	Delivery is completely assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).