



**Order number:** 389XP-4SP-R-7016

**Manufacturer:** Briefkasten Manufaktur Lippe

ab **€3,329.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



## free-standing letterbox with showcase BASIC Plus 389X ST-T with bell box - 710x660 - RAL of your choice

High quality showcase made in Germany by Briefkasten Manufaktur. The ideal solution for simple poster display indoors and outdoors.

The showcase is completely made of aluminum, powder coated in RAL color. The showcase is suitable for 2x DIN A-4 sheets, the showcase has a RAL color, magnetic back wall and a white text panel in the upper viewing area. The glazing is made of single-pane safety glass, the integrated ventilation openings ensure against fogging of the pane.

The letterbox is made of stainless steel V2A, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this free-standing letterbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail holding bracket and the very robust lock distinguish this free-standing letterbox. The side panel with protruding rain cover made of stainless steel V2A offers optimal protection against the weather and guarantees a very high durability. The installation box allows easy mounting of a built-in speaker for an intercom system. Optionally, the mailbox is available with an integrated and preconfigured video intercom system from COMELIT. The letterboxes of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The construction has been developed by our own engineers with regard to high flexibility or modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

### • free-standing letterbox with bell box & showcase, powder coated in RAL color

- The system is manufactured at Briefkasten Manufaktur. German quality production "Made in Germany".
- The mailbox complies with DIN/EN 13724. Throw-in size (3.5 cm x 32.5 cm) for C4 crosswise, large letters fit in here without bending.
- Insertion flap with noise-damping rubber seal for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate (type 2) under the access flap and mail holding bracket.

### • Showcase made of aluminum, powder coated in RAL color

- Suitable for 2x DIN A-4 sheets.
- Glazing made of single-pane safety glass / ESG. Integrated ventilation openings against fogging of the pane.
- The visible area has a surface of W 560 x H 520mm minus text panel H 80mm.
- Text panel made of white acrylic text panel, removable, without text. The text panel can be easily covered with labeling foil. Illumination in environmentally friendly, energy-saving LED technology possible.
- The door can be opened from left to right with safety lock incl. 2 keys.
- Magnetic back panel in RAL color.
- Angular aluminum frame construction with internal corner connectors (no plastic!).
- Incl. side panel + rain roof made of stainless steel V2A, powder coated in RAL color.

### • Bell box made of stainless steel V2A, powder coated in RAL color

- Speech hole with universal adapter. (Intercom system / built-in speaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 14 mm (lateral right). Invisible cable routing through the stand element.
- The stand elements are made of aluminum profile, powder coated in RAL color for screw mounting or for setting in concrete.

### Important information

#### Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

#### Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

### Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel, Aluminum
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	66,0
Width letterbox system in cm:	106,5
Overall height in cm:	120,0   160,0
Total width in cm:	114,5
Depth in cm:	10,0
Weight in kg:	39,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).