





2-compartment free-standing letterbox Design BASIC 381 ST-R with bell box & newspaper box- RAL 7016 anthracite

The 2 parties free-standing letterbox BASIC with closed newspaper compartment, to be operated with a toggle lock. The mailbox is made of galvanized steel, powder coated in anthracite gray RAL 7016, the stand elements are made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the well thought-out concept make this free-standing letterbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail holding bracket and the very robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

- · 2-compartment free-standing letterbox made of galvanized steel, powder coated in anthracite-gray RAL 7016
- The system is made at the letterbox manufactory. German quality production "Made in Germany".
- The mailbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber seal for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- Newspaper box with door and toggle lock, powder coated in anthracite gray RAL 7016. Adhesive lettering "ZEITUNG" white. Dimensions: 355x165x100mm.
- Additional rain protection is achieved by the optional rain protection roof made of stainless steel V2A, powder coated in anthracite gray RAL 7016.
- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.
- Speech-bell part made of galvanized steel, powder painted in anthracite-gray RAL 7016
- · Speech perforation with universal adapter. (Intercom system/built-in loudspeaker not included).
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- · Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.
- The stand elements are made of 42.4 mm V2A stainless steel 1.4301, ground for screw mounting or setting in concrete. **Important information:**

Mail is only protected from moisture and dirt when fully inserted and the flap is closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Shipping information:

Number of parties:	2
Item withdrawal:	Front
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	99,0
Width letterbox system in cm:	35,5
Overall height in cm:	120,0 150,0
Total width in cm:	53,5
Depth in cm:	10,0 15,0
Weight in kg:	30,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment.

mailboxes, the stand & box can be shipped separately).

Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing