



# 2-compartment Stainless steel mailbox column Designer BIG - GIRA System 106 - 3-compartment prepared - house number illuminated - RAL of your choice

High-quality manufactured 2 party mailbox column made of stainless steel V2A 1.4301, powder coated in RAL fine structure matt with backlit house number of the brand Briefkasten Manufaktur. The Gira System 106 can be inserted laterally, seamlessly in flush design. The preparation is intended for 3 pieces GIRA 106 system modules. The modules can be used flush with the surface thanks to the simple holding system (surface-mounted housing 5503910 required!).

The column is fully welded, so no rivets or screws are visible. The letterbox module is also inserted into the pillar with invisible screws. The letterbox module is made of 2mm stainless steel V2A 1.4301, powder coated in RAL fine structure matt and can be exchanged for a new letterbox module even after many years. This letterbox stele is manufactured at Briefkasten Manufaktur. Made in Germany, Bad Salzuflen.

- The 2 party mailbox module is made of 2mm stainless steel V2A 1.4301, powder coated in RAL color.
- Front mail removal door 350 mm x 300 mm, to open from top to bottom. Incl. 2 keys with key number.
- Mail slot from front, dimensions of slot: W 35 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without bending.
- With built-in damping elements, these let the insertion flap close slowly and quietly.
- The columns are equipped with modules that can be replaced later.
- House number approx. 70-100mm high (max. 3 digits) with power-saving LED lighting 12V DC approx. 50mA / 1W, white.
- Incl. EVN LED power supply / transformer IP65 12V/DC 0,1-4W for the LED lighting.
- The fully welded column is made of 1.5mm stainless steel V2A 1.4301, powder coated in RAL color. Overall height is 1.70m.
- Invisible cable feed through the body is possible.
- The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. Thus, the mounting dowels are concealed.
- WITHOUT GIRA system components!

#### Important information

#### Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

### Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy.

Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

## Abmessungen & Details

Number of parties:	2
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	71,0   75,0
Width single box in cm:	41,0   45,0
Volume single box in liters:	: 31,0
Height letter slot in cm:	6,3
Width letter slot in cm:	32,0
Overall height in cm:	170,0
Total width in cm:	49.0 (footplate 58.0)
Depth in cm:	15.0 (footplate 24.0)
Weight in kg:	65,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.