



Order number: 380BP-SP-7016-550

Manufacturer: Briefkasten Manufaktur Lippe

X

This product is currently not available.

ab **€1,219.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Large free-standing letterbox Design BASIC 380BP-550 ST-T with bell box - RAL 7016 Anthracite-Grey

Modern large capacity letterbox for free standing with cladding and rain roof - made in Germany by Briefkasten Manufaktur.

This mailbox is suitable for particularly large mail volumes in the business environment or in the absence of several days in private households. The bell box is suitable for a standard built-in speaker and is complemented by the high-quality stainless steel bell button.

The letterboxes made of galvanized steel, powder-coated in RAL 7016 anthracite gray, the stand elements made of anodized aluminum profile, powder-coated are solidly manufactured and at the same time very elegant. A close-fitting side panel with rain cover made of 2mm stainless steel, the rain gutters for optimal water protection, a throw-in flap with rubber lip, the solid change name plate and the robust lock characterize this free-standing letterbox. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

• free-standing letterbox completely powder-coated in RAL 7016 anthracite gray fine structure matte

- The system is made at the letterbox manufactory. German quality production "Made in Germany".
- This large capacity mailbox is suitable for increased mail volume with 77 liters.
- The mailboxes are made of galvanized steel, powder coated in RAL 7016 anthracite gray fine structure matt comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number and change name plate under the access flap per mailbox.
- Incl. close-fitting side panel + rain cover made of stainless steel V2A, powder coated in RAL 7016 anthracite gray fine structure matt.
- Optional house number inscription, lasered approx. 80-100mm high.

• Bell box made of stainless steel, powder-coated in RAL 7016 anthracite gray

- Intercom hole with universal adapter. (Intercom system / built-in speaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 1x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplates are dent-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 14 mm (lateral right). Invisible cable routing through the stand element.
- The stand elements are made of aluminum profile, powder coated in anthracite gray RAL 7016 fine structure, matt for screw mounting or for setting in concrete.

Important information:

Mail is only protected from moisture and dirt when fully inserted and the flap is closed. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Optional components



Optionally, our letterbox systems are also available including a video intercom set from COMELIT. The COMELIT video intercom sets are completely pre-wired and programmed by us, so the set is ready for connection. Only 2 wires to connect!

The intercom sets from COMELIT are simply connected with the 2-wire technology. This means that the existing lines can be used and there are no additional costs for laying new lines and plastering or painting work. From the new power supply unit in the meter cabinet, simply lay 2 wires to the built-in loudspeaker in the function box of the letterbox system, as well as 2 wires from the power supply unit to the door station in the apartment. DONE.

++ ideal for conversion and renovation, as existing bell lines can be used

++ no additional effort for plastering and painting

++ low costs due to simple installation

++ simple commissioning

++ including handicap function at the door

++ can be expanded at any time to include handicap-suitable monitors for hearing aid users

Video intercom set

• Door station 6741W with mobile function

• Color monitor with 4.3" screen 16/9, hands-free full-duplex and touch-sensitive buttons. Allows brightness, contrast control and adjustment of the strength of the audio signal and ring tone. There are several melodies to choose from to personalize the ringtone. Standard equipment with buttons for door opener, for activation/deactivation of voice connection with corresponding LED indicators. Door station with Wifi interface for simulation of domestic Presence: in combination with the COMELIT app, door calls can be answered from anywhere and doors and gates can be opened. Face recognition for contactless access is possible with the COMELIT app. Dimensions: 160 x 115 x 22 mm (WHT).

• Video speaker 4681 with holder 1250U switch

• Color audio-video unit for 2-wire system, complete with front adjustable LED illuminated color camera. Equipped with terminal block, speech connection with echo cancellation, dustproof and waterproof loudspeaker, electret microphone and loudspeaker volume adjustable at the front. Additional visual and audible programmable handicap indicators. Integrated electronic door opener function (3 A) and additional relay contacts C, NC, NO with 10 A. Dimensions: 102 x 55 x 38 mm (WHT)

• 2-wire power supply 1209

• Power supply unit for 2-wire systems for the supply of the landing station (terminals L1 - L1) and the rising line (terminals L2 - L2). Equipped with a terminal for line termination. Input voltage 110-240 V AC. Note: The power supply does not provide an interface for connecting external lighting such as for nameplates or similar. Dimensions: 106 x 89 x 62 mm (WHT) (6 DIN modules)

• COMELIT pushbutton with nameplate

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Steel galvanized, Aluminum
Height single box in cm:	55,0
Width single box in cm:	37,0
Volume single box in liters:	77,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	66,0
Width letterbox system in cm:	37,0
Overall height in cm:	120,0 160,0
Total width in cm:	47,0
Depth in cm:	43,5
Weight in kg:	37,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).