Briefkasten Manufaktur® Lippe GmbH



4-compartment Stainless steel surface mailbox Design BASIC Plus 382XA AP with bell box- RAL of your choice

High quality surface mailbox for 4 parties made in Germany by Briefkasten Manufaktur.

The mailbox is made entirely of stainless steel V2A, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this mailbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail holding bracket and the very robust lock distinguish this surface-mounted mailbox.

The letterboxes of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The design has been developed by our own engineers with a view to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

4-compartment Surface-mounted mailbox made of stainless steel V2A, powder-coated in RAL color

• The letterbox is made at the letterbox manufactory. German quality production "Made in Germany".

• The mailbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

• Insertion flap with noise-damping rubber seal for very quiet insertion of mail.

• The door can be opened from left to right.

• Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.

• Large capacity due to optional letterbox depth +50 mm = approx. 17 I. Suitable for companies and households with very large mail volumes.

• Incl. side panel + rain cover made of stainless steel V2A, powder coated in RAL color.

· Speech-bell part made of stainless steel V2A, powder coated in RAL color

• Speech perforation with universal adapter. (Intercom system / built-in loudspeaker not included in delivery). Optionally also without speech perforation.

• Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

• Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).

• Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.

• For wall mounting incl. mounting material (screws + dowels). For fence mounting also available without perforation on the back (perforation must be provided by customer).

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	4
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	: 76,0
Width letterbox system in cm:	71,0
Depth in cm:	10,0 15,0
Weight in kg:	34,0
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing

mailboxes, the stand & box can be shipped separately).