



**Order number:** 1250.2

**Manufacturer:** GIRA

ab **€96.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



## home station AP

home station freely as a pre-assembled unit for wall-mounted assembly.

- Completely pre-assembled home station wall-mounted, therefore fast and clean installation.
- Design variety through integration into the switch program, which means that uniform appearance of door communication and electrical installation.
- assembly with and without a cover frame.
- one-piece assembly by plug-in screw terminals on the assembly plate. The contact to the home station is contacted on the assembly plate when the living station is plugged in.
- dismantling of the home station during renovation work.
- fastening holes for assembly.
- Signal transmission and supply of the home station via polarity-proof and short-circuit-resistant 2-wire bus.
- parallel circuit of up to three home stations possible (for voltage supply via 2-wire-bus).
- one-man commissioning through one-piece commissioning procedure.
- call tone difference between door call, internal call and floor call.
- Selection of five different fragrance onmelodies that can be individually assigned to individual call buttons.
- hands-free function (voice-controlled interpretation with echo and background noise suppression).
- enforcement function for loud ambient noise during the speech connection.
- co-hearing.
- control buttons with integrated luminaire for the state display.

**The control buttons of the Home station AP control the following functions in connection with the switch actor or the Built-in-Schaltaktor:**

- switching of light and other functions.
- Control of the door opener.
- Setting the call one melody.
- ruin tone on and off.
- call acceptance.
- activation of the enforcement function.
- Setting call tone and speech volume.

### technical data

**power supply:** 26 V DC  $\pm$  2 V (bus voltage)

#### connections:

2 screw clamps 2-wire-bus

2 screw clamps base call button

/> **temperature range:** -5 ° C to +50 ° C

### Notes

- assembly possible without cover frames.
- For assembly with system 55 or the switch programs surface switch and E22, a cover frame is required in 2 without the middle bracket.
- When installing on a device dinner, a cover frame is required
- With this component, the construction of door communication systems with up to 70 participants is possible (e.g. 1 x installation speaker, 5 x expansion module for installation speakers, 68 x Home-Station AP).

## Abmessungen & Details

**Connection technology:** 2-wire bus technology

**Depth in cm:** 2,0

**Width in cm:** 5,5

**Height in cm:** 12,7