





Order number: 555-BEKA-35-VAR-KSDBE
Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,129.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Stainless steel mail slot with DoorBird video intercom - slot 350x63mm - 410x375mm

High-quality manufactured mailbox cover with letter slot of the brand Mailbox Manufacture. Integrated DoorBird IP video door station D2100E or D1100E. The DoorBird IP Video Door Station D2100E or D1100E is the smart solution for your front door. The IP Video Door Station can be operated as a standalone unit or integrated into an existing smart home platform. Even existing, classic installations such as a door chime or an electric door and gate opener can continue to be used with DoorBird and controlled via the app.

This is a real eye-catcher among mailboxes. Clean lines and no-frills design characterize the designer mailbox collection. Our products have a high value, reliable functionality and their own identity. Made by Briefkasten Manufaktur. DoorBird was also not only invented and developed in Germany, but is also produced in Berlin to this day. At DoorBird, "Made in Germany" is not just a seal, but a lived philosophy. The IP video door stations are manufactured in the DoorBird manufactory to guarantee the highest quality, durability and customer satisfaction.

- Stainless steel letter slot made of 2 mm stainless steel V2A 1.4301, powder coated in RAL color.
- Throw-in flap is created at the letterbox manufactory. German quality production "Made in Germany".
- Throw-in size suitable for C4 crosswise. Here fit very large letters and magazines without bending pure.
- Optionally with house number, backlit in white incl. EVN LED power supply / transformer IP65 12V/DC 0.1-4W for the LED lighting of the house number.
- Incl. DoorBird IP video door station D2100E or D1100E installed.
- Mounting is via four supplied stainless steel screws incl. dowels.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy. Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Base material:	Stainless steel
Connection technology:	LAN
Height in cm:	37,5
Width in cm:	41,0
Height letter slot in cm:	6,3
Width letter slot in cm:	35,0
Weight in kg:	8,0
Delivery condition:	Delivery is assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).