



Order number: 1239.2

Manufacturer: GIRA

ab **€699.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



home station Video AP Plus GIRA in different colors

Home station Video with 5.6 cm TFT color display (2.2 ") and capacitive control buttons as a pre-assembled unit for wall-mounted assembly. An SD memory card is included in the scope of delivery for internal image memory.

- When using a voltage supply for door communication, up to 28 home stations can be used in parallel.
- The Home Station Video AP automatically recognizes whether a voltage supply for door communication is connected. A bridge between ZV and bus is not necessary.
- Color display with LED backlight.
- OSD function, d. H. Text glare in the display for the status display and menu navigation.
- capacitive control buttons with integrated luminous emissions for the state display: The keys are served by slight touch.
- Switch-on door opener automatic door: If the function is switched on, the door opener is automatically controlled after pressing the door station call button.
- Automatic call acceptance: address directly in or listen to a room after internal call.
- free-free in-house speech with up to ten other home stations.

The control buttons of the Home Station Video AP control the following functions:

- Manual on and off of the TFT color display.
- camera circuit-targeted selection of the connected color cameras. The text display takes place in the display, which camera is currently being controlled.
- switching of light and other functions in connection with the switch actor or the Built-in-switch actor.
- Control of the door opener.
- ruin tone on and off.
- call acceptance.
- activation of the enforcement function.
- Setting call tone and speech volume.

functions in the end customer menu

- internal call, switching act, call one melody, brightness, color saturation, contrast, switch-on time of the display, language (21 languages ☐selectable), button tones, automatic door opener (after installer release), automatic call acceptance (after installation approval).
- Internal image memory (after installation approval) for up to 48 pictures. Manual transmission internal to external image memory (SD memory card). Delete the image memory manually. Trigger manual snapshot. Rename switching stores and internal calls. Change date/time.

Additional functions in the installer menu:

- Setting main/support display, frequency setting, scheduling of the line, version display, factory setting, switching on or off, switching on or off the display, switching on or off, call button assignment, assigning internal calls, releases for automatic door and automatic call acceptance.
- card slot for SD memory card.
- SD memory card.
- release of the internal image storage. Setting the image interval and the recording speed. Set date/time.

Properties of the SD memory card:

- directory for ten ringtones, five of them freely configurable in wave format. Folders for external image memory (max. 200 pictures).

technical data

voltage supply: DC 26 V \pm 2 V (via 2-wire bus)

Connections

2-wire bus: 2 x screw clamp

Bowlage call button: 2 x screw clamp

Additional supply: 2 x screw clamp

Display size: 2.2 "

Color system: pal

resolution: 320 x 240 (H x V), QVGA

SD memory card

Format: FAT32

Image memory: Max. 200 Images

Ruftonmelodien: 10, of which 5 are freely selected (Wave format)

Notes

- assembly without cover frame or with cover frame 2-part without an intermediate bridge from the switch programs system 55, surface switch or E22 possible.

dimensions & details

Abmessungen & Details

Connection technology: 2-wire bus technology

Depth in cm: 2,0

Width in cm: 5,5

Height in cm: 12,7