



Order number: 384Q-VA-2-SP-ZFG-100

Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,167.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



2-compartment Stainless steel free-standing letterbox Design BASIC 384 ST-Q with bell box & newspaper compartment

High-quality stainless steel free-standing letterbox for 2 parties made in Germany by Briefkasten Manufaktur.

The complete mailbox system is made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this stainless steel mailbox system our top seller. A rain drainage edge for optimum water protection, a double-edged insertion flap with rubber buffer, the solid change name plate, a practical mail holding bracket and the very robust lock distinguish this stainless steel letterbox system.

Thanks to the construction method, self-assembly is uncomplicated.

• 2-compartment free-standing letterbox made of weatherproof V2A stainless steel 1.4301, grinded

- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insert size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.
- Insertion flaps with noise-dampening rubber buffers for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- 2x newspaper compartment with door and toggle lock made of stainless steel V2A 1.4301, ground. Laser inscription "ZEITUNG" black. Dimensions: 355x165x100mm.
- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volume.
- Additional rain protection is achieved by the optional rain protection roof made of stainless steel V2A, ground.
- **Speech-bell part made of weatherproof V2A stainless steel 1.4301, grinded**
- Speech hole with universal adapter. (Intercom system / built-in loudspeaker not included in delivery). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 2x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1,5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplate is dent and impact resistant, the plastic is flame retardant.
- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.
- The stand elements are made of 40x40mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, installation and wiring.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	2
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	109,0
Width letterbox system in cm:	35,5
Overall height in cm:	150,0
Total width in cm:	43,5
Depth in cm:	10,0 15,0
Weight in kg:	15,0
Delivery condition:	Delivery takes place in blocks, Stand elements/letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).