



Order number: 599BPK-VAR-KSCSWIFI-R

Note: After your order, you will receive a design drawing by email as a PDF to realize your wishes even to the last detail. Here, your wishes will be addressed in detail.

Datasheet for Stainless steel mailbox package column designer BIG - RAL to choose -Comelit VIDEO Komplettset Wifi

Manufacturer: Briefkasten Manufaktur Lippe

ab **€5,859.00** *

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Briefkasten Manufaktur® Lippe GmbH

Datasheet for Stainless steel mailbox package column designer BIG - RAL to choose -Comelit VIDEO Komplettset Wifi



Stainless steel mailbox package column Designer BIG - RAL of your choice - Comelit VIDEO Komplettset Wifi

Modern stainless steel column made of 2 mm stainless steel V2A 1.4301, powder coated in RAL color of your choice. Integrated Comelit VIDEO complete set Wifi. Comelit video intercom is an innovative solution with features such as face recognition, Voice commands and operation via app with your smartphone. Completely pre-programmed for easy installation - connect 2 wires and DONE!

The column is fully welded, so no rivets or screws are visible. The mailbox module and parcel box module are also inserted into the pillar with invisible screws. The letterbox and parcel box modules are also made of 2mm stainless steel V2A 1.4301, powder coated in RAL color and can be replaced with new modules even after many years. This mailbox stele with parcel box is manufactured at Briefkasten Manufaktur. Made in Germany, Bad Salzuflen.

Parcel reception independent of the delivery person! Every parcel deliverer (e.g. DHL, UPS, DPD, TNT, GLS, Hermes, etc.) can use this parcel box.

Mailbox module made of 2mm stainless steel V2A 1.4301, powder coated in RAL of your choice

• Front mail removal door 350 mm x 300 mm, to open from top to bottom. Incl. 2 keys with key number.

• Mail slot from front, dimensions of slot: W 35 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without bending. Attention no removal protection!

- · Insertion flap with built-in damping elements, these let the insertion flap close slowly and quietly.
- Incl. Comelit video intercom with bell push button made of stainless steel incl. change name plate, illuminated installed.
- Optionally with house number, backlit in white incl. EVN LED power supply / transformer IP65 12V/DC 0.1-4W for the LED lighting of the house number.

• Parcel box module made of 2mm stainless steel V2A 1.4301, powder coated in RAL of your choice

• Volume parcel box: 130 liters, Max. Parcel size: 540 x 690 x 340 mm (WHT). Ideal for large parcels, suitable for one-time use until the next emptying.

• Front mail removal door 510 mm x 660 mm, to open from left to right. Incl. 5 keys with key number.

- The parcel removal door is equipped with high quality stainless steel hinges for extremely long durability.
- Innovative package lock with snap-in latch.
- High quality stainless steel laser inscription "PAKET".
- The letterbox and parcel box modules of this pillar can also be replaced later, so you always remain flexible.
- The fully welded column is made of 2 mm stainless steel V2A 1.4301, powder coated in RAL color
- Overall height is 1.70 m.
- Invisible cable feed through the body is possible.

• The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. This way the fixing dowels are concealed.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

To achieve optimum water protection for your mail, the mailbox or mailbox system should be located under a canopy if possible. Mail is only protected from water when it is completely deposited in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Connection technology:	2-wire bus technology
Height single box in cm:	BK 51.0 55.0 - PK 71.0 75.0
Width single box in cm:	BK 56.0 60.0 - PK 56.0 60.0
Volume single box in liters:	BK 31.0 PK 130.0
Height letter slot in cm:	6,3
Width letter slot in cm:	35,0
Overall height in cm:	170,0
Total width in cm:	64.0 (footplate 73.0)
Depth in cm:	35.2 (footplate 44.2)
Weight in kg:	95,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.