



Order number: 382XA-E2-KSCSWIFI-1-100 Manufacturer: Briefkasten Manufaktur Lippe

### ab **€1,561.00** \*

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Briefkasten Manufaktur® Lippe GmbH



# Stainless steel surface mailbox BASIC Plus 382XU Elegance II - Comelit VIDEO complete set Wifi - RAL of your choice

Modern surface mailbox with wifi-enabled video intercom from Comelit - made in Germany by Briefkasten Manufaktur. Complemented by the design fascia Elegance with a discreet dividing line, a house number and name inscription as a high-quality laser inscription in gray font color.

The mailbox is made entirely of stainless steel V2A 1.4301, powder coated in RAL color. The very high quality workmanship and the sophisticated concept make this surface mailbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, a practical mail holding bracket and the very robust lock distinguish this surface mailbox. The side panel and the rain cover are made of stainless steel V2A and thus guarantee a very high durability. Integrated Comelit video intercom including apartment station with an integrated Wifi system for mobile access via app from your smartphone.

The letterbox systems of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The design has been developed by our own engineers with regard to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

#### • Surface-mounted mailbox completely made of stainless steel V2A 1.4301, powder-coated in RAL color of your choice

• The system is made at the Briefkasten Manufaktur. German quality production "Made in Germany".

• The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

- Insertion flap with noise-damping rubber seal for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number and mail holding bracket.

• Large capacity due to optional mailbox depth +50 mm = approx. 17 I. Suitable for companies and households with very large mail volumes.

• Cover made of stainless steel V2A 1.4301, ground. Optionally with laser inscription in gray. House number approx. 80-100mm height & name inscription approx. 15-25mm height.

#### · Bell box made of stainless steel V2A, powder coated in RAL color of your choice

- 8-12V DC short stroke bell push button with LED ring illumination in white.
- Side panel and rain roof made of stainless steel V2A, powder coated in RAL color.

• Optionally for wall mounting incl. mounting material (screws + dowels), for fence mounting with rod mat holder or without hole for on-site mounting hole.

#### Important information

#### Camera or intercom preparation

## Intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

#### Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

#### **Abmessungen & Details**

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Connection technology:	2-wire bus technology
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0   17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm	: 66,0
Overall height in cm:	recommended 150.0 - 170.0
Depth in cm:	10,0   15,0
Weight in kg:	12,0
Delivery condition:	Plant is delivered pre-assembled/partially disassembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).