




Order number: 382XU-VA-3S-SP-100-O
Manufacturer: Briefkasten Manufaktur Lippe

ab **€821.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



2-compartment 1x2 stainless steel flush-mounted mailbox BASIC Plus 382XU UP with bell box - polished stainless steel

Modern 2-compartment flush-mounted mailbox with bell box for intercom (optional camera) - made in Germany by Briefkasten Manufaktur.

The mailbox is made entirely of stainless steel V2A 1.4301, 240 grain ground. The very high quality workmanship and the sophisticated concept make this flush-mounted mailbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid changeable name plate, a practical mail holding bracket and the very robust lock characterize this flush-mounted mailbox. The flush-mounted frame made of stainless steel V2A is equipped with a foam rubber seal and guarantees a very high durability.

The letterboxes of the BASIC Plus collection are characterized by the consistent use of stainless steel V2A. The result is a very high durability and sustainability. The design has been developed by our own engineers with a view to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

• 2-compartment Flush-mounted letterbox completely made of stainless steel V2A 1.4301, 240 grain ground

- The system is manufactured at Briefkasten Manufaktur. German quality production "Made in Germany".
- The mailboxes comply with DIN/EN 13724. Insert size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

- Insertion flaps with noise-damping rubber seal for very quiet insertion of mail.

- The doors can be opened from left to right.

- Incl. 2 keys with key number, changeable name plate (type 2) under the insertion flap and mail holding bracket per party.

- Large capacity due to optional mailbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.

• Bell box made of stainless steel V2A 1.4301, 240 grain grinded

- Speech perforation with universal adapter. (Intercom system/built-in loudspeaker not included). Optionally also without speech perforation.

- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).

- Anti-vandalism - the nameplate (type 1) is dent-proof and impact-resistant, the plastic is flame-retardant.

- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, 240 grain ground.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	3
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	114,0
Width letterbox system in cm:	40,5
Depth in cm:	10,0 15,0
Weight in kg:	25,0
Delivery condition:	Delivery is completely assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).