



**Order number:** 529SST-VA-KSCSA-1

**Manufacturer:** Briefkasten Manufaktur Lippe

ab **€1,191.00** \*

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Die Anschlussleitung mit 8P-Schwerlaststecker  
zu verwenden. Bitte vorher prüfen!



Fußplatte erhält bei Montage zum Einbautieren

#### MONTAGEHILFE

Wir empfehlen bei freistehenden Anlagen folgende Fundamente aus Beton (B20), Maße pro Cerebante 450 x 450 mm. Bei kleineren Anlagen wird ein durchgehendes Fundament mit folgenden Maßen benötigt: Abgabehöhe + 450 x 450 mm. Je nach Bodenbeschaffenheit ist das Fundament zu vergrößern. Die Fundamenttiefe sollte mindestens 700 mm betragen, je nach Frosttiefe im Boden. Die Einbauleitung für das Störgeräusch sollte 200 mm - 500 mm betragen. Vor Aufbau ist es ratsam, einen Spaltspaten über den geplanten Montageort beim gegebenen Anlauf anzuhaken, damit Bodenwölben, Elektroableitung usw. nicht beschädigt werden.

Bitte achten Sie vor dem Betreiben auf das Einziehen der Kabel. Wird die Anlage auf ein Betonfundament aufgesteckt, müssen dazu Schwerlastanker (Durchmesser 10 mm) oder gleichwertig verwendet werden.

## Stainless steel doorbell freestanding DESIGNER 529S ST-R Elegance I - Comelit AUDIO Komplettsset

This simple and at the same time elegant doorbell pedestal has a built-in Comelit door intercom system including home station. The front panel made of stainless steel V2A 1.4301, polished is placed on a 5mm stainless steel frame and stands out slightly in this respect from stand elements made of stainless steel polished.

Our products have a high value, reliable functionality and their own identity. Made by Briefkasten Manufaktur.

- Door station made of 2 mm stainless steel V2A 1.4301, 240 grain polished.
- Installation box made of 2 mm stainless steel V2A 1.4301, 240 grain ground.
- Dimensions of doorbell plate W 160 mm x H 320 mm x D 8 mm.
- Dimensions of installation box: W 130 mm x H 290 mm x D 50 mm
- 8-12V DC short-stroke bell pushbutton with LED ring illumination in white.
- Incl. Comelit audio speaker 1621 with holder 1250U switch, 2-wire power supply 1210 and audio home station 6750W.
- The pedestals are made of 42.4 mm stainless steel, polished. Invisible cable routing through the columns.

### Important information

#### Camera or intercom preparation

**The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, installation and wiring.**

#### Water protection

For optimum water protection, the door station should be located under a canopy if possible.

### Abmessungen & Details

<b>Number of parties:</b>	1
<b>Base material:</b>	Stainless steel
<b>Connection technology:</b>	2-wire bus technology
<b>Number of bell buttons:</b>	1
<b>Height in cm:</b>	29,0   32,0
<b>Width in cm:</b>	13,0   16,0
<b>Overall height in cm:</b>	120,0   150,0   170,0
<b>Total width in cm:</b>	29,0
<b>Depth in cm:</b>	5,2
<b>Weight in kg:</b>	4,0
<b>Delivery condition:</b>	Delivery is made in blocks, stand elements/door station divided
<b>Shipping information:</b>	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).