



Order number: 870-VAR-KSCSWIFI-1-160 Manufacturer: Briefkasten Manufaktur Lippe


ab **€1,202.00** *

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Briefkasten Manufaktur® Lippe GmbH

Datasheet for Bell pillar bell designer - stainless steel V2A - RAL to choose - Comelit VIDEO Komplettset Wifi





Bell pillar Bell pillar designer - stainless steel V2A - RAL of your choice - Comelit VIDEO Komplettset Wifi

High quality manufactured bell pillar completely made of stainless steel V2A, powder coated of the brand Briefkasten Manufaktur. Integrated Comelit video intercom including apartment station with an integrated Wifi system for mobile access via app from your smartphone.

Our products have a high value, reliable functionality and their own identity. Made by Mailbox Manufacture.

• Bell pillar made of 1.5 mm stainless steel V2A 1.4301, powder coated.

• The system is made by Briefkasten Manufaktur. German quality production "Made in Germany".

• The speaking part is made of 2mm stainless steel V2A 1.4301, powder coated. Dimensions: W 190 mm x H 640 mm x D 110 mm.

• 8-12V DC short stroke bell push button with LED ring illumination in white.

Optional house number approx. 70mm high (max. 3 digits) optionally with power-saving LED illumination 12V DC approx. 50mA / 1W, white or as laser engraving.

1W, white or as laser engraving.

• Incl. 6x screws cover caps made of stainless steel V2A, ground, so that the screws for fixing the front panel are not visible. See pictures.

• The fully welded column is made of 1.5mm stainless steel V2A 1.4301, powder coated. Construction height is either 1.30 m or 1.60 m.

• The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. See pictures.

• Invisible cable feed through the body is possible.

• Including video speaker 4681 with holder 1250U-Switch, 2-wire power supply 1209 and video home station 6741W.

Important information

Camera or intercom preparation

Intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy.

Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Base material:	Stainless steel
Connection technology:	2-wire bus technology
Height single box in cm:	64,0
Width single box in cm:	19,0
Overall height in cm:	130,0 160,0
Total width in cm:	22.0 (footplate 32.0)
Depth in cm:	11.0 (footplate 21.0)
Weight in kg:	40,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.