# Briefkasten Manufaktur® Lippe GmbH

#### Datasheet for Stainless steel mailbox free-standing designer organic Big ST-R- Clean Edition- individually



## stainless steel mailbox freestanding designer organic Big ST-R- Clean Editionindividually

High quality mailbox free-standing the brand mailbox manufactory with extra volume (21 liters) & extra large throw-in (6.3cm x 35cm). This is a real eye-catcher among the mailboxes. Organic lines and straightforward design are characterized by the designer Organic mailbox. Our products have a high value, reliable functionality and their own identity. Made by mailbox manufactory.

very high quality manual work!

• The mailbox consists of 2mm stainless steel V2A 1.4301, 240 grain ground; Dimensions: height 780 mm; Width: 480 mm; Depth 100 mm.

- Fronts side post-withdrawal door 350 mm x 300 mm, to open from top to bottom. Including 2 key with key number.
- Settling from the front, dimensions of the insertion: W 35 cm x H 6.3 cm, C4 across. Here, very large letters fit without kinking.
- with built-in damping elements, which let the throw-in flap slowly and quietly close.
- optionally interchangeable name tag made of stainless steel with laser lettering or name tag made of plexi.

• Optionally with house number in polished optics (67mm high), offset or house number approx. 70mm high (max. 3-digit) with powersaving LED lighting 12V DC approx. 50mA / 1W, white.

• 8-12V DC Kurzhub bell button with LED ring lighting (blue, white, red or green). The lighting of the bell button cannot be supplied by the control unit. It must be connected to an additional power supply 8-12 V DC.

- Optional is an 8-12V DC short-lived light button with pictogram.
- Preparation (installation speaker not included) for intercom.
- Optional with universal adapter for all commercially available installation speakers.
- Optional preparation (not in the scope of delivery) for a camera.

• The stand columns consist of 60.3 mm stainless steel V2A 1,4301. Invisible cable routing through the stand columns.

### important information

### camera or voice center preparation

#### We always recommend the electrical installation to be carried out by an electrical installer.

We offer the preparation of cameras & speakers from different manufacturers for our mailboxes. The preparation does not contain any end devices, which are the provision of the screw recordings, bores and perforations. So that you can easily install your device. water protection

In order to achieve optimal water protection of your post, the mailbox or the mailbox system should be under a canopy if possible. The post office is only protected from water if it is completely stored in the box and the throw-in flap is closed. Unskined mail enables the penetration of moisture and dirt into the mailbox. It is therefore necessary to plan sufficiently dimensioned mailboxes for the upcoming need. In certain extreme weather conditions, water can still occur (according to DIN EN 13724 to 1ccm). This is not a reason for complaint.

### Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	71,0   78,0
Width single box in cm:	41,0   48,0
Volume single box in liters:	21,0
Height letter slot in cm:	6,3
Width letter slot in cm:	35,0
Overall height in cm:	120,0   150,0   170,0
Total width in cm:	57,0
Depth in cm:	10,0
Weight in kg:	35,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).