## Briefkasten Manufaktur<sup>®</sup> Lippe GmbH

#### Datasheet for Video module Ultra with blind button for rear with external buttons incl. power supply 1210A - RAL color



Order number: 1299-KSUT2020-HB-MP Manufacturer: Comelit

### ab **€622.00 \***

incl. VAT <u>plus shipping costs</u> (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



# Video module Ultra with dummy button for rear mounting with external pushbuttons incl. power supply 1210A - RAL of your choice

Comelit video module Ultra for rear mounting in mailbox systems with external pushbuttons (pushbutton interface Ultra 3063U required, not included), the digital call module Ultra or the touch screen module Ultra.

Audio/video unit in RAL/DB color of choice.

• 2-wire system, just plug in 2 wires and go.

• Wide angle camera (H120° x V90° field of view) with high resolution (1288 x 968 pixels).

• LED illumination of the camera. Due to the integrated infrared LEDs under the camera lens, all visitors are optimally displayed even at night.

Omni-directional digital microphone and two speakers for hi-fi audio.

Additional visual and audible indicators for handicapped, adjustable in programming.

• Integrated relay allows door or gate openers to be connected directly through the module. The door and gate openers are

controlled via the indoor station or via your smartphone or tablet via app.

• Protection class IP65 and IK08.

• Module for rear installation in our fascia boards and letterbox systems.

• Incl. power supply unit 1210A (optional accessories required: push button interface Ultra 3063U, digital call module Ultra, touch screen module Ultra, home station video 6741W, 6721W or 6801W).

• Recommended installation height: 1350-1600mm.

### Important information

### Camera or intercom preparation

Intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

### Abmessungen & Details

Base material:	Aluminum
Connection technology	: 2-wire bus technology
Height in cm:	Outstation 9.0   Power supply 8.9
Width in cm:	Outstation 10.0   Power supply unit 14.1
Depth in cm:	Outstation 3.5   Power supply unit 6.2
Weight in kg:	2,0
Delivery condition:	Delivery is assembled
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).