



Order number: 1298-D1100E

Manufacturer: Doorbird

ab **€645.87 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users
with VAT ID and Non-EU countries)



DoorBird IP Video Door Station D1100E for integration purposes - Engineering Edition

Imagine you are just not at home and your children have locked themselves out or the parcel carrier brings a delivery. With DoorBird this is no longer a problem. Every time the doorbell rings, you get a push notification on your smartphone or tablet and can talk to the visitor and see him in HD quality. So you are guaranteed not to miss a visitor anymore. With DoorBird, you are on the go but still at home, even if a burglar rings the doorbell to check presence.

For integration purposes in our mailbox systems and tableaux. Doorbell buttons are not included, these are sold separately.

Open API

- Local interface for integration with third party and SIP systems

Video and audio call

- On smartphones and tablets (iOS, Android) or landline phones (SIP)

Smart Transmission Mode (STM)

- Real-time audio / video transmission optimized for mobile devices over WLAN, 3G, 4G, 5G

Smart Home & ONVIF compatible

- KNX, Loxone, Synology, KIWI AVM FRITZ!Fon, URC, Bang & Olufsen, Control4, QNAP, RTI, ELAN, Fibaro and many more.

Individual time and action plans, e.g.:

- 4D motion detector turns on external lamp between 9 p.m. and 6 a.m

Automatic door opener

- For use in office and practice environments

Free cloud recording

- Optionally activatable for visitor history

Geofencing

- Automatic gate and door opening when returning home

Burglary prevention

- Prevents more break-ins than an alarm system

Receive parcels at any time

- Direct the parcel delivery person to the neighbor's house or open the garage door by smartphone

Night vision

- With 12 IR LEDs

Light sensor

- For night vision mode

Motion sensor with 4D technology

- Distance up to 10 m adjustable via app (interval: 1 m)

HDTV video

- High-end ultra-wide angle hemispherical lens 200° (D), 150° (H), 90° (V), rectified, IR-capable
- HDTV 1080p, dynamic (VGA - HDTV)

Echo and noise cancellation (AEC, ANR)

Bluetooth

- Bluetooth Low Energy (BLE), activatable with future firmware and app update

Easy connection to the network

- Connection via network cable or bell wire (with 2-wire transformer) to RJ45 jack (PoE, network data)
- Connection via WLAN

One freely configurable bistable switching relay

- One door or gate controllable via app
- State configurable via app: temporary or permanent switching

Abmessungen & Details

Connection technology: LAN, WLAN

Height in cm: 11,52

Width in cm: 5,4

Depth in cm: 2,845

Weight in kg: 0,19