



Order number: 599B-VAR-KSCSUWI

Note: After your order, you will receive a design drawing by email as a PDF to realize your wishes even to the last detail. Here, your wishes will be addressed in detail.

Manufacturer: Briefkasten Manufaktur Lippe

ab **€3,459.00** *

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

Stainless steel mailbox column Designer BIG - RAL of your choice - 2-wire - VIDEO complete set Ultra WiFi

Stylish stainless steel column made of stainless steel V2A 1.4301, powder coated in RAL/DB color in extra large format. With a newspaper drop flap suitable for newspapers, magazines and book mail. Integrated Comelit VIDEO complete set Ultra with WiFi function. The Comelit video intercom is an innovative solution with features such as face recognition, voice commands and operation via app with your smartphone. Completely pre-programmed for easy installation - connect 2 wires and DONE!

The column is fully welded, so no rivets or screws are visible. The letterbox module is also inserted into the pillar with invisible screws. The letterbox module is also made of 2mm stainless steel V2A 1.4301, powder coated in RAL fine structure matt and can be exchanged for a new letterbox module even after many years. This mailbox stele is manufactured at Briefkasten Manufaktur. Made in Germany, Bad Salzuflen.

- The letterbox module is made of 2mm stainless steel V2A 1.4301, powder coated in RAL/DB of your choice.
- 2-wire system with high-resolution wide-angle camera (H120° x V90° field of view, resolution 1288 x 968 pixels), door opener function and app connection.
- With single button including bell symbol centered in the middle and name labeling centered at the top.
- Front-side mail removal door 350 mm x 300 mm, to be opened from top to bottom. Incl. 2 keys with key number.
- Mail slot from front, dimensions of slot: W 35 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without bending.
- With built-in damping elements, these let the insertion flap close slowly and quietly.
- The columns are equipped with modules that can be replaced later.
- Optionally with house number, backlit in white incl. EVN LED power supply / transformer IP65 12V/DC 0.1-4W for the LED lighting of the house number.
- The fully welded column is made of 1.5mm stainless steel V2A 1.4301, powder coated in RAL color. Construction height is 1.70 m.
- Invisible cable feed through the body is possible.
- The pillar is equipped with a base plate made of VA. This is 10 mm thick and is finished with a cover plate. This way the fixing dowels are hidden.
- Incl. home station 6741W with mobile function and power supply unit 1210A.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

In order to achieve optimum water protection for your mail, the mailbox or mailbox system should, if possible, be located under a canopy.

Mail is only protected from water when it is completely deposited in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. Therefore, it is necessary to plan sufficiently sized mailboxes for the upcoming needs. In certain extreme weather conditions, water can still enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Connection technology:	2-wire bus technology
Height single box in cm:	71,0 75,0
Width single box in cm:	41,0 45,0
Volume single box in liters:	31,0
Height letter slot in cm:	6,3
Width letter slot in cm:	35,0
Overall height in cm:	170,0
Total width in cm:	49.0 (footplate 58.0)
Depth in cm:	15.0 (footplate 24.0)
Weight in kg:	65,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.