



Order number: 382A-VA-1-SP-ZFG-100

Manufacturer: Briefkasten Manufaktur Lippe

ab **€684.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Stainless steel surface mailbox Design BASIC 382A AP with bell box & newspaper compartment closed

The complete surface-mounted mailbox is made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this stainless steel mailbox our top seller. A rain drainage edge for optimum water protection, a double-edged access flap with rubber buffer, the solid change name plate, a practical post holder and the very robust lock distinguish this stainless steel mailbox. This high-quality stainless steel surface mailbox is only available from us.

• Letterbox made of weather-resistant V2A stainless steel 1.4301, ground.

- The system is created at the letterbox manufactory. German quality production "Made in Germany".
- Newspaper box with door and toggle lock made of stainless steel V2A 1.4301, ground. Adhesive inscription "ZEITUNG" black. Dimensions: 355x165x100mm.

• The mailbox complies with DIN/EN 13724. Insert size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

- Large capacity due to optional letterbox depth +50 mm = approx. 17 l. Suitable for companies and households with very large mail volumes.
- Insertion flap with noise-damping rubber buffers for very quiet insertion of mail.
- Door opens from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail retaining bracket.
- Incl. rain protection roof, flush at the back and protruding to the front, made of stainless steel V2A, polished.

• Speech bell part made of weatherproof V2A stainless steel 1.4301, polished

- Speech hole with universal adapter. (Intercom system / built-in speaker not included). Optionally also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.
- For wall mounting (incl. mounting material)

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	59,5
Width letterbox system in cm:	35,5
Depth in cm:	10,0
Weight in kg:	12,0

Shipping information: Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).