



**Order number:** 1299-KSUT8020-HB-MP-OTA

**Manufacturer:** Comelit

ab **€1,149.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)

## IP Video Module Ultra - Polished Aluminum

- Audio/video unit in aluminum, polished.
- IP system, just plug in LAN cable and go.
- Wide angle camera (H160° x V100° field of view) with HD resolution.
- LED illumination of the camera. The integrated infrared LEDs under the camera lens make it easy to see all visitors even at night.
- Omni-directional digital microphone and two speakers for hi-fi audio.
- Additional visual and audible indicators for handicapped, adjustable in the programming.
- The 2 integrated relays allow door or gate openers to be connected directly through the module. The control of the 2 door and gate openers is done via the indoor station or via your smartphone or tablet via app.
- Protection class IP65 and IK08.
- Module for rear mounting in our fascia boards and letterbox systems.
- Optional accessories required (see accessories): Button cover, Button interface Ultra 3063U(for external buttons), 1440 Switch, 1441 Power supply PoE, Digital call module Ultra, Touchscreen module Ultra, Home station video 6742W, 6722W, 6842W or 6802W.
- Recommended installation height: 1350-1600mm.

The VIP system is the evolution of video intercoms and related services related services. The services meet all modern requirements of buildings used for residential, commercial, industrial and industry-related services buildings: from single-family houses to building complexes, both new buildings and reconstructions or renovations of old buildings. It is designed for the Unlimited number of subscribers and allows simultaneous allows simultaneous calls without distance limitations. The devices are connected to a single, dedicated or existing network via RJ45. Devices are connected via RJ45. In the ViP system, all devices are connected to the (dedicated or shared) LAN network, from the remote site to the most distant indoor station Indoor station. Compared to the traditional analog video intercom systems, the digital network protocol enables easy Configuration of the system without costly or complex measures. Even system upgrades are extremely versatile and practical executable. Installation, commissioning and reconfiguration can be carried out in the And reconfigurations can be carried out easily and completely securely on the network.

### Important information

#### Camera or intercom preparation

The intercom systems must be connected by an electrical installer. Contact your trusted electrical installer for planning, installation and setup.

### Abmessungen & Details

<b>Base material:</b>	Aluminum
<b>Connection technology:</b>	LAN
<b>Height in cm:</b>	Outstation 9.0   Power supply 8.9
<b>Width in cm:</b>	Outstation 10.0   Power supply unit 14.1
<b>Depth in cm:</b>	Outstation 3.5   Power supply unit 6.2
<b>Weight in kg:</b>	2,0
<b>Delivery condition:</b>	Delivery is assembled
<b>Shipping information:</b>	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).