



**Order number:** 381-K7016-1-SP-ZF

**Manufacturer:** Briefkasten Manufaktur Lippe

ab **€689.00 \***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Zur Verschraubung sind M10 Schwenkanker  
zu verwenden. Diese werden nicht mitgeliefert.



## Mailbox, freestanding design BASIC 381 - anthracite gray RAL 7016 with bell box & newspaper tube

Modern free-standing letterbox made in Germany by Briefkasten Manufaktur.

The mailbox is made of galvanized steel, powder coated in RAL color fine structure matt, the stand elements are made of weather-resistant stainless steel V2A, ground. The very high quality workmanship and the sophisticated concept make this free-standing letterbox our top seller. A rain drainage edge for optimal water protection, a continuous rubber lip for quiet insertion, the solid interchangeable name plate, a practical mail holding bracket and the very robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

• **free-standing letterbox made of galvanized steel, powder-coated in RAL color fine structure matt**

- The system is made at the mailbox manufactory. German quality production "Made in Germany".
- The mailbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

- Insertion flaps with noise-damping rubber seal for very quiet insertion of mail.

- The door can be opened from left to right.

- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.

- Newspaper compartment, open on both sides made of stainless steel V2A, powder coated in RAL color fine structure matt.

Dimensions: 355x100x100mm.

- Additional rain protection can be achieved by the optional rain protection roof made of stainless steel V2A, polished.

• **Bell box made of galvanized steel, powder coated in RAL color fine structure matt**

- Speech hole with universal adapter. (Intercom system/built-in loudspeaker not included). Optionally also available without speech perforation.

- Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).

- Anti-vandalism - the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.

- Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.

- The stand elements are made of 42.4 mm V2A stainless steel 1.4301, ground for screw mounting or setting in concrete.

### Important information

#### Camera or intercom preparation

**The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, installation and wiring.**

#### Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

### Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Steel galvanized, Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm:	53,0
Width letterbox system in cm:	35,5
Overall height in cm:	120.0   150.0 + 7.0 attached rain canopy
Total width in cm:	53,5
Depth in cm:	10,0
Weight in kg:	21,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).