



Order number: 592BPK-VAR-R

Note: After your order, you will receive a design drawing by email as a PDF to realize your wishes even to the last detail. Here, your wishes will be addressed in detail.

Manufacturer: Briefkasten Manufaktur Lippe

ab **€4,819.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Eingebaute Dämpfungselemente lassen die Einwurflappe langsam und leise schließen



Stainless steel parcel post box Designer BIG for surface mounting - RAL of your choice - optionally with camera and built-in loudspeaker

Modern parcel post box made of 2 mm stainless steel V2A 1.4301, powder-coated in RAL colour of choice. The body is fully welded, so no rivets or screws are visible. The letterbox module and the parcel box module are also inserted into the corpus with invisible screws. The letterbox and parcel box modules are also made of 2mm stainless steel V2A 1.4301, powder-coated in RAL colour and can be exchanged for new modules even after many years. This parcel post box is manufactured at Briefkasten Manufaktur. Made in Germany, Bad Salzuflen.

Parcel reception independent of the delivery person! Every parcel delivery company (e.g. DHL, UPS, DPD, TNT, GLS, Hermes, etc.) can use this parcel box.

• Parcel post box made of 2mm stainless steel V2A 1.4301, powder-coated in RAL of your choice

- Front-side mail removal metre 350 mm x 300 mm, to be opened from top to bottom. Incl. 2 keys with key number.
- Post insertion from the front, dimensions insertion: W 35 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without bending.
- Insertion flap with built-in damping elements, these allow the insertion flap to close slowly and quietly.
- Optional replaceable name plate made of stainless steel with laser inscription or name plate made of Plexi.
- Optionally with house number in polished optics (67mm high), offset mounted or house number illuminated.
- 8-12V DC short-stroke bell push button with LED ring illumination (blue, white, red or green). The illumination of the bell push button cannot be supplied via the control unit. It must be connected to an additional power supply 8-12 V DC.
- Optionally, an 8-12V DC short-stroke light button with pictogram is possible.
- Preparation (built-in speaker not included) for intercom possible.
- Optional with universal adapter for all commercially available built-in speakers.
- Optional preparation (camera not included) for a camera.

• Parcel box module made of 2mm stainless steel V2A 1.4301, powder-coated in RAL of choice

- Volume parcel compartment: 130 litres, Max. Parcel dimensions: 540 x 690 x 340 mm (WHT). Ideal for large parcels, suitable for one-time use until the next emptying.
- Front-side mail removal opening 510 mm x 660 mm, to be opened from left to right. Incl. 5 keys with key number.
- The parcel removal door is equipped with high-quality stainless steel hinges for extremely long durability.
- Innovative parcel lock with snap-in catch.
- High-quality stainless steel laser inscription "PAKET".
- The letterbox and parcel box modules can also be exchanged later, so you always remain flexible.
- **The fully welded body is made of 2 mm stainless steel V2A 1.4301, powder-coated in RAL colour**
- Invisible cable routing through the body is possible.
- For wall mounting with mounting rail for very easy installation.

Important information

Camera or intercom preparation

Intercom systems must be connected by an electrician. Contact your trusted electrician for planning, installation and wiring.

Water protection

For optimum water protection of your mail, the letterbox or letterbox system should, if possible, be located under a canopy.

The mail is only protected from water if it is completely deposited in the box and the access flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming demand. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	1
Item withdrawal:	Front
Base material:	Stainless steel
Height single box in cm:	BK 51.0 55.0 - PK 71.0 75.0
Width single box in cm:	BK 56.0 60.0 - PK 56.0 60.0
Volume single box in liters:	BK 31.0 PK 130.0
Height letter slot in cm:	6,3
Width letter slot in cm:	35,0
Overall height in cm:	134,0
Total width in cm:	64,0
Depth in cm:	35.2 (mounting rail + 1.2)
Weight in kg:	65,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.