Briefkasten Manufaktur[®] Lippe GmbH



5-compartment 3x2 letterbox system freestanding design BASIC 381-K7016 - anthracite-gray RAL 7016 with bell intercom part

High quality free-standing letterbox for 5 parties made in Germany by Briefkasten Manufaktur.

The mailbox is made of galvanized steel, powder coated in anthracite-gray RAL 7016, the stand elements are made of weatherresistant stainless steel V2A, ground. The very high quality workmanship and the well thought-out concept make this free-standing letterbox our top seller. A rain drainage edge for optimal water protection, a throw-in flap with rubber seal, the solid changeable name plate, a practical mail holding bracket and the very robust lock distinguish this free-standing letterbox. This mailbox is easy to clean and insensitive.

Thanks to the construction method, self-assembly is uncomplicated.

• 5-compartment free-standing letterbox made of galvanized steel, powder coated in anthracite-gray RAL 7016

• The system is made at the letterbox manufactory. German quality production "Made in Germany".

• The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 crosswise, here fit even large letters without bending.

• Insertion flaps with noise-damping rubber lip for very quiet insertion of mail.

- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the access flap and mail holding bracket per mailbox.
- Optional newspaper compartments, open on both sides, made of galvanized steel, powder coated in anthracite gray RAL 7016.

• Large capacity due to optional letterbox depth +50 mm = approx. 17 I. Suitable for companies and households with very large mail volumes.

• Additional rain protection is achieved by the optional rain protection roof made of stainless steel V2A.

• Speech-bell part made of galvanized steel, powder coated in anthracite-gray RAL 7016

• Speech perforation with universal adapter. (Intercom system / built-in loudspeaker not included). Optionally also available without speech perforation.

• Universal adapter is suitable for all commercially available built-in speakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).

- 3x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism the nameplate is dent-proof and impact-resistant, the plastic is flame-retardant.

• Cable access: Ø 10.4 mm (right side). Invisible cable routing through the stand element.

• The stand elements are made of 42.4 mm V2A stainless steel 1.4301, ground for screw mounting or for setting in concrete. Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, mounting and installation.

Water protection

Mail is protected from moisture and contamination only when it is fully inserted and the flap is closed. In certain extreme weather conditions, water may nevertheless enter (according to DIN EN 13724 up to 1ccm). This is not a reason for complaint.

Abmessungen & Details

Number of parties:	5
Item withdrawal:	Front
Base material:	Steel galvanized, Stainless steel
Height single box in cm:	33,0
Width single box in cm:	35,5
Volume single box in liters:	12,0 17,0
Height letter slot in cm:	3,5
Width letter slot in cm:	32,5
Height letterbox system in cm	: 109,0
Width letterbox system in cm:	71,0
Overall height in cm:	150.0 + 7.0 attached rain roof
Total width in cm:	89,0
Depth in cm:	10,0 15,0
Weight in kg:	68,0
Delivery condition:	Delivery is made in blocks, stand elements / letterbox divided
Shipping information:	Depending on the order volume, delivery is made by parcel shipment or bulky goods shipment. Partial deliveries are possible for products that can be disassembled (e.g., for floor-standing mailboxes, the stand & box can be shipped separately).