



Order number: 215-AP-4


Manufacturer: Briefkasten Manufaktur Lippe

ab **€1,641.00 ***

incl. VAT [plus shipping costs](#) (exclusive of VAT for logged-in users with VAT ID and Non-EU countries)



Montageschiene
für eine einfache
Montage



4-compartment 2x2 design surface mailbox system GOETHE AP - RAL of your choice

High-quality manufactured 4 parties surface-mounted mailbox system. The modern letterbox GOETHE is ideal for the sophisticated entrance area. The linear design without a visible lock makes this mailbox look particularly elegant.

The dimensions of the individual boxes allow a capacity of approx. 16 liters, the large insertion guarantees no crumpled mail even with DIN C4 envelopes and magazines or after several days of absence. The innovative push-key lock is invisibly hidden inside the mailbox. The key is simply inserted into the existing opening (no turning required) and the door opens. With the arrangement of the lock, this mailbox is designed so that the removal door prevents mail from falling towards you. Due to the water drainage edge, the mail inside is optimally protected from the weather. The insertion flap is equipped with high-quality axle dampers, so quiet closing is guaranteed and there is no annoying rattling due to weather influences. The exchangeable name plates made of Plexiglas can be operated comfortably from the front, for an optimal optic we recommend the flush name plate with laser engraving (see accessories). The 2nd name plate is equipped with the insert advertising Yes/No.

The surface-mounted letterboxes of the GOETHE collection are characterized by the consistent use of stainless steel and aluminum. The result is very high durability and sustainability. The design has been developed by our own engineers with regard to high flexibility or modularity, easy spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are directly available in our store.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5

- High-quality 4-compartment surface-mounted mailbox made of stainless steel and aluminum.
- Quality production - Made in Germany by Briefkasten Manufaktur Lippe.
- Mailboxes made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder coated in RAL of your choice.
- Innovative push-key lock with 2 keys per party.
- Letter insertion and removal from the front. Insertion flap with high-quality axle dampers for very quiet insertion of mail.
- The mailboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 crosswise, large letters also fit in here without bending.
- Removal doors open from top to bottom. So the mail can not fall against you.
- Name plate made of Plexiglas for name inscription and 2nd name plate advertising Yes/No per party.
- Optional house number inscription approx. 70-80mm high.
- Optimal rain protection due to rain protection edges and a rain canopy made of 3mm aluminum AlMg3 W19, powder coated in RAL of your choice.
- Side cladding made of 3mm aluminum AlMg3 W19, powder coated in RAL of your choice.
- Incl. mounting rail for wall mounting.

Important information:

To achieve optimum water protection for your mail, the mailbox or mailbox system should be located under a canopy if possible. Mail is only protected from water when it is completely inserted in the box and the insertion flap is closed. Mail that is not completely inserted allows moisture and dirt to enter the mailbox. This system is protected against water ingress in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Abmessungen & Details

Number of parties:	4
Item withdrawal:	Front
Base material:	Stainless steel, Aluminum
Height single box in cm:	40,0
Width single box in cm:	40,0
Volume single box in liters:	16,0
Height letter slot in cm:	3,5
Width letter slot in cm:	36,0
Height letterbox system in cm:	80,0
Width letterbox system in cm:	80,0
Total width in cm:	80,8
Depth in cm:	10.0 + 2.5 Rain roof
Weight in kg:	29,0
Delivery condition:	Delivery is assembled
Shipping information:	Delivery by forwarding agent on one-way pallet. Before delivery, the forwarding agent will contact you by phone to arrange the date.