2-unit stainless-steel surface-mounted mailbox BASIC Plus 382X AP with side-mounted bell box | Left | 150mm depth | with 2 letterboxes (2x1) | Stainless steel, brushed



Product number 382XA-2W-SP-150-L

Product description

2-unit stainless steel surface-mounted mailbox BASIC Plus 382X AP with side bell box

German quality manufacturing "Made in Germany" by Briefkasten Manufaktur. The complete 2-unit surface-mounted mailbox is made of weather-resistant stainless steel V2A, brushed. A rain drip edge for optimal water protection, a double-folded mail flap with rubber buffer, the solid interchangeable nameplate, a practical mail retention bar and the robust lock characterise this stainless-steel mailbox.

The mailbox systems of the BASIC Plus collection are characterised by the consistent use of stainless steel V2A. The result is very high durability and sustainability. The construction has been developed by our own engineers with a focus on high flexibility and modularity, easy spare-part installation and straightforward self-installation. Spare parts for all BASIC Plus systems are available directly.

Thanks to the construction, self-installation is straightforward. The mailbox system is prepared for uncomplicated complete installation; there is no need for complex wall mounting of individual boxes. 2-unit surface-mounted mailbox made of high-quality, weather-resistant stainless steel V2 A 1.4301, brushed.

The advantages at a glance

Close-fitting stainless-steel cladding with rain canopy

Side cladding and rain canopy are included in this version and are made of stainless steel V2A, brushed. The close-fitting design forms a unified, constructively coordinated unit with the mailbox system.

Generous letter insertion

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

The insertion opening measures 35 × 325 mm and is designed for DIN C4 landscape. The mailbox version complies with DIN EN 13724.

Quiet insertion and comfortable removal

The integrated flap damping with rubber buffer reduces impact noise during insertion. The mail retention bar holds items back during removal.

Integrated bell and intercom area

Bell box made of stainless steel V2A 1.4301, brushed. The stainless-steel bell push Type 4 is used. Optionally prepared with a speaking grille for the installation of standard intercom systems or flush-mounted speakers. (Intercom system/flush-mounted speaker not included). An option with the Comelit Ultra video complete set is also available.

Quality manufacturing and considered construction

The system is manufactured by Briefkasten Manufaktur in Germany. The construction is designed for straightforward self-installation.

Equipment and product details

Mailbox system

Number of mailboxes 2 separate mail compartments
Arrangement 2 × 1
Depth 150 mm
Mailbox material Stainless steel V2A 1.4301
Mailbox surface Brushed
Bell/intercom unit Bell box made of stainless steel V2A 1.4301, brushed

Mail and operation

Insertion opening 35 × 325 mm, suitable for DIN C4 landscape
Standard DIN EN 13724
Insertion flap Noise-damped by rubber buffer
Keys 2 keys with key number per mailbox
Nameplate Interchangeable nameplate below the insertion flap
Mail retention bar Integrated in each mailbox

Mounting and fittings

Mounting type Surface-mounted
Rain drip edge Integrated into the construction
Rain canopy Made of stainless steel V2A, brushed
Side cladding Made of stainless steel V2A, brushed
Mounting material For wall mounting including mounting rail and fixing material (screws + wall plugs)
Manufacture Made in Germany by Briefkasten Manufaktur Lippe

Note on weather protection

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

Mail items are best protected against moisture and soiling when fully inserted and with the insertion flap closed. Protruding items can prevent the flap from fully closing.

Note on wall mounting

Before installation, the load-bearing capacity and condition of the wall must be checked. Fixings must be matched to the system weight and the existing wall construction.

Product properties

Series	BASIC
Number of bell push buttons	1 button, 2 buttons, 3 buttons
Functions	Light button, Intercom
Functional box prepared for manufacturer	GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald, Legrand Bticino, Comelit
Name labelling	Nameplate
Material	Stainless steel V2A 1.4301
Number of boxes	with 2 letterboxes
Removal of mail	On the front
Surface/colour	Brushed
Boxes by volume	Large > 16 litres
Mounting type	Surface-mounted

Dimensions

Height of single box in mm	330.0
Width of single box in mm	355.0
Capacity in litres	12.0 | 17.0
Height of letterbox slot in mm	35.0
Width of letter slot in mm	325.0
Height of letterbox in mm	330.0
Width of letterbox system in mm	880.0
Total width in mm	880.0
Depth in mm	100.0 | 150.0
Weight in kg	12

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

More images









Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618









Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618