DoorBird Multi-Tenant Module MTM14E for External Pushbuttons

Product number 1298-DBMTM14E



Product description

DoorBird MTM14E multi-tenant module for external call buttons

The DoorBird MTM14E multi-tenant module enables the connection of up to 14 third-party call buttons with LED lighting. It is suitable for DoorBird D2100E and D2100EA IP video door stations as well as the D21x series without keypad, providing a flexible solution for multi-tenant buildings, customised doorbell panels and bespoke entrance-area installations.

External call buttons from almost any manufacturer can be connected via the MTM14E's digital inputs. The connected buttons must be volt-free. Connection options for LED lighting of the call buttons are available. Incandescent (filament) bulbs are not supported, as they draw too much current.

Flexible integration into custom door stations

The multi-tenant module is particularly suitable when a DoorBird IP video door station is to be combined with external call buttons selected for design or site-specific reasons. This allows DoorBird door communication solutions to be integrated into custom-made mailbox systems, doorbell panels or existing front plates.

Technical specifications

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

Product	DoorBird MTM14E multi-tenant module
Function	For the connection of up to 14 third-party call buttons with LED lighting
Compatibility	DoorBird D2100E and D2100EA IP video door stations D21x series without keypad
Connections	14 x screw terminal connectors (sockets and plugs) with four pins E, E: Digital input 0 V, 0 A (NO), for push-button switches V-: Negative pole for call button LED lighting V+: Positive pole for call button LED lighting, 5 V DC, 9 V DC or 12 V DC, max. 5 mA Door station: Connection to the door station
D21x series connection	Connect to the door station's red cable
Call buttons	Volt-free call buttons required
Call button lighting	Only suitable for LED lighting; incandescent (filament) bulbs are not supported
Approvals	IP40
Weatherproof	No
Weight	65 g
EAN	4260423866836
Scope of delivery	1 x DoorBird MTM14E multi-tenant module

Notes

- The connected call buttons must be volt-free.
- Only call buttons with LED lighting may be connected; incandescent (filament) bulbs are not supported.
- Connecting an analogue door gong to the digital inputs for push-button switches is not supported.
- If a door gong is required, use the DoorBird IP door gong A1061W or the DoorBird IP video indoor station A1101.
- The module is not weatherproof and must be installed in a suitably protected location.
- Installation must be carried out by a qualified electrician.

Dimensions

Width in mm	15
Height in mm	40.6
Total width in mm	15
Depth in mm	131.7

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

More images

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618