Gira audio REG control device 128700



Product number 128700

Product description

Audio REG control device

Control device for supplying the audio components of the Gira door communication bus.

- Supply of the reverse-polarity protected and short-circuit-proof 2-wire bus.
- Self-resetting electronic short-circuit and overload detection of the operating voltages and the bus connection.
- Buttons for system and door release programming.
- LED status indicators for operation, overload, system programming and door opener programming.
- AC 12 V output for the power supply of a standard electric strike.
- Permanent AC 12 V output for supplying power to a DCS-TC gateway.
- Relay output for switching a door opener with its own power supply.
- Door opener switching time continuously adjustable from 1 to 10 s.

Technical data

Nominal voltage primary: 230 V AC, 50 Hz
Secondary rated voltage: SELV 26 V DC ±2 V
Secondary rated current: 160 mA continuous load, 550 mA peak load (max. 5 s), overload cut-out from 350 mA
Screw terminals: 0.6 mm to 2.5 mm²
Door opener output: 12 V AC, 1.6 A / ED 25 %
Relay output: 30 V AC/DC, 2 A
Total cable length: max. 700 m
Cable length from the control unit to the furthest participant: max. 300 m with cable ø 0.8 mm, max. 170 m with cable ø 0.6 mm
Dimensions: REG device with 6 TE
Temperature range: -5 °C to +45 °C
Protection class: IP 20

Notes

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

- The audio control device is intended for installation in the sub-distribution board. If this is not possible, use a standard surface-mounted distributor.
- This component can be used to set up door communication systems with up to 70 users (e.g. 1 x built-in loudspeaker, 5 x extension module for built-in loudspeakers, 68 x surface-mounted home station).

Dimensions

Width in mm	108 (6TE)
Height in mm	REG
Depth in mm	65,0
Weight in kg	0,2

More images

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618