Gira System 106 IP speech module, brushed stainless steel | Stainless steel, brushed

Product number S106-5592920-VA



Product description

Gira System 106 IP Speech Module brushed stainless steel

The **Gira System 106 IP Speech Module** is a central communication module for modern **door stations** in the **Gira System 106**. It enables high-quality audio communication between indoor and outdoor areas in **HD quality** and supports a convenient **full-duplex hands-free function**. This allows conversations to take place naturally, clearly and without mutual interruptions.

For reliable voice transmission the module features **two integrated microphones** as well as a **weatherproof speaker**. Even with increased ambient noise, comprehension remains good because disturbing background sounds are effectively reduced by **Active Noise Cancelling (ANC)**. This makes the IP speech module particularly interesting for entrance areas of residential and commercial buildings with elevated noise levels.

Power is supplied via **Power over Ethernet (PoE)**. This simplifies installation because data transmission and power supply are combined over the network connection. At the same time, the IP speech module supplies power to other **System 106 modules** of the door station and thus performs an important function within the entire door communication system.

Key features

- Speech module for the **Gira IP door communication** in System 106
- High-quality audio communication in **HD quality**
- **Full-duplex hands-free** for natural conversation
- Two integrated microphones and weatherproof speaker
- **Active Noise Cancelling (ANC)** to reduce ambient noise
- Power supply via **PoE**
- Supplies power to other modules of the **Gira System 106 door station**

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

Technical data

Power supply	PoE via RJ45, PoE standard IEEE 802.3af-2003, IEEE 802.3at-2009, IEEE 802.3bt-2018-1; only power injectors with a maximum output power of 30 W may be used
Protection class	III (SELV)
Power consumption (standby)	1.75 W
Power consumption (audio talk state)	2.50 W
Power consumption (video talk state)	2.76 W
Network / PoE connection	RJ45 (must be used only in conjunction with the supplied patch cable)
Connections for video components	1 x camera module connection, 1 x call display module connection
System connections	2 x connector strips
Ambient temperature	-20 °C to +50 °C

Application area

The **IP speech module for Gira System 106** is suitable for high-quality door communication solutions in the private and commercial sectors. It is particularly useful where clear voice transmission, structured system integration and a robust design for outdoor use are required.

Product properties

Connection technology	LAN
Material	Stainless steel V2A 1.4301
Surface/colour	Brushed

Dimensions

Width in mm	106.5
Height in mm	106.5
Total width in mm	106.5
Depth in mm	2,0
Weight in kg	1

More images

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618