# DoorBird IP VIDEO Flat Station A1103 | Black

**Product number** 1298-A1103-B




## Product description

## DoorBird IP Video Indoor Station A1103 Black Edition

The DoorBird IP Video Indoor Station A1103 Black Edition is a modern indoor station for IP-based door communication in residential, commercial and public buildings. In conjunction with a DoorBird IP Video door station it enables live video, two-way audio and the control of doors, gates, elevators and other connected functions.

The 7-inch True IPS touch display offers a clear presentation and an intuitive user interface. The black finish in polycarbonate and glass blends discreetly into modern interiors. In addition to touch operation, the indoor station features a touch bar with main functions and a configurable RGB LED status bar for visitor and event signals.

**Flexible IP door communication for modern buildings**

The DoorBird A1103 supports network connection via LAN, Wi-Fi and PoE. With multiple indoor stations, room-to-room communication can be used. Additional features include SIP support, visitor history with free cloud recording, weather forecast and functions for home and building automation control via IP, TCP, HTTPS and relays.

**Integrated relays and digital inputs**

Two freely configurable bistable latching relays can be used to control, for example, electric door openers, gates or elevators. Two digital inputs allow the integration of floor-call buttons or other potential-free contacts. Configuration is carried out via the DoorBird app or the web-based dashboard.

### Technical data

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

| | |
|---|---|
| **Product** | DoorBird IP Video Indoor Station A1103 Black Edition |
| **Finish** | Black |
| **Material** | Polycarbonate, glass |
| **Mounting type** | Surface mounting<br>Desk stand available separately |
| **Power supply** | 15 - 48 V DC, min. 15 W, or Power over Ethernet, PoE 802.3af Mode-A |
| **Power consumption** | Max. 10 W |
| **Operating conditions** | 0 °C to +55 °C<br>Relative humidity 0% to 85%, non?condensing |
| **Connections** | RJ45 for LAN/PoE<br>Digital input #1, 0 V, 0 A (NO), e.g. for floor-call button<br>Digital input #2, 0 V, 0 A (NO), e.g. for second floor-call button<br>Bistable self?holding relay #1, max. 24 V DC / AC, 1 A<br>Bistable self?holding relay #2, max. 24 V DC / AC, 1 A<br>15 - 48 V DC input (+, -), max. 15 W |
| **Relays** | 2 x freely configurable bistable latching relays, e.g. for electric door openers, gates or elevators |
| **Digital inputs** | 2 x potential?free digital inputs, e.g. for floor-call buttons |
| **Display** | 7-inch True Color LCD |
| **Touchscreen** | Yes, capacitive |
| **Resolution** | 1024 x 600 pixels |
| **IPS** | Yes |
| **Glass** | Scratch?resistant hardened glass |
| **Audio** | Speaker and microphone<br>Echo and noise suppression, AEC and ANR<br>Two?way audio |
| **Volume** | HD audio, up to 102 dB |
| **Ringtones** | More than 50 ringtones |
| **Operation** | Touch display<br>Touch bar with main functions<br>Configurable tile view<br>Configurable RGB LED status bar |
| **Ethernet** | 10/100 Base?T, PoE capable |
| **Wi-Fi** | 802.11 b/g/n, 2.4 GHz |
| **Wireless modules** | Wi?Fi 802.11 b/g/n, 2.4 GHz |
| **IP functions** | Door opening and elevator control<br>Visitor history with free cloud recording<br>Room?to?room communication with multiple indoor stations<br>SIP support, e.g. for concierge or caretaker call<br>Weather forecast<br>Home and building automation control via IP, TCP, HTTPS and relays<br>Compatible with smart locks and DoorBird IP Video Mini Dome camera<br>Configuration via DoorBird app and web?based dashboard |
| **System requirements** | Mobile device with current iOS or Android<br>High?speed fixed?line broadband connection via DSL, cable or fibre<br>No SOCKS or proxy server<br>Ethernet network with DHCP |

| | |
|---|---|
| **Supported door stations** | Any DoorBird IP Video door station |
| **Approvals** | CE RED, IEC/EN 62368, FCC, IC, Reach 250, RoHS 2.0, California 65, WEEE |
| **Weight** | 510 g |
| **EAN** | 4251489614011 |
| **Manufacturer's item number** | 429614011 |
| **Scope of delivery** | 1 x IP Video indoor station<br>1 x mounting bracket<br>1 x mains adapter 100 - 240 V AC to 15 V DC with up to 4 country adapters<br>1 x quick start guide with digital passport<br>1 x installation manual<br>1 x small parts |

### Notes

- The DoorBird IP Video Indoor Station A1103 Black Edition is intended for indoor use.
- Connection can be via LAN, Wi-Fi or PoE.
- The desk stand is optional and not included in the scope of delivery.
- With multiple indoor stations, room-to-room communication can be used.
- Installation must be carried out by a qualified electrician.

## Dimensions

| | |
|---|---|
| **Width in mm** | 185.0 |
| **Height in mm** | 146.0 |
| **Total width in mm** | 185.0 |
| **Depth in mm** | 26.04 |
| **Weight in kg** | 0,4 |

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

# More images










Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618