Gira video amplifier 122200

Product number 122200



Product description

Gira video amplifier

The video amplifier is used to extend the range in Gira door communication systems with video function. It raises the level of the incoming video signal to the maximum permitted bus level and outputs this at the output. This compensates for the line attenuation from the source of the video signal to the input of the video amplifier.

The combined housing allows three types of installation

- Surface-mounted (in a standard junction box).
- Flush-mounted (in an appliance box).
- As a REG device (with the enclosed REG adapter).

Technical data

Connections

2-wire bus IN: 2 x screw terminal
2-wire bus OUT: 2 x screw terminal

Ambient temperature: -25 °C to +70 °C

Notes

- With the video amplifier, the maximum cable length between the door and home station can be extended from 100 to 300 metres.
- No further configuration is required during commissioning, as the video amplifier automatically adapts to the existing cable network.

Dimensions

Width in mm	36
Height in mm	52
Depth in mm	27,0
Weight in kg	0,2

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618

More images

Briefkasten Manufaktur Lippe GmbH
Werler Straße 60
32105 Bad Salzuflen

www.briefkasten-manufaktur.de
info@briefkasten-manufaktur.de
Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck
Ust.ID.Nr. DE303690847
Handelsregister Amtsgericht Lemgo, HRB 8618